



SETRON, Switch disconnecter 3LD, emergency switching-off switch, 3- pole, Iu: 25 A, operating power / at AC-23 A 400 V: 9.5 kW, front-mounted, 1 NC, 1 NO, rotary operating mechanism, Red / yellow, 4-hole mounting of the handle

| Model                                                                               |                                        |
|-------------------------------------------------------------------------------------|----------------------------------------|
| product brand name                                                                  | SETRON                                 |
| product designation                                                                 | Switch disconnecter                    |
| design of the product                                                               | EMERGENCY-STOP switch                  |
| display version for switch position indicator manual operation                      | 1 ON - 0 OFF                           |
| type of switch                                                                      | front mounted                          |
| design of the actuating element                                                     | Short rotary knob                      |
| color of the actuating element                                                      | red                                    |
| design of handle                                                                    | rotary operating mechanism, red/yellow |
| type of the driving mechanism motor drive                                           | No                                     |
| General technical data                                                              |                                        |
| number of poles                                                                     | 3                                      |
| size of switch disconnecter                                                         | 2                                      |
| mechanical service life (operating cycles) typical                                  | 100 000                                |
| electrical endurance (operating cycles)                                             |                                        |
| • at AC-23 A at 690 V                                                               | 6 000                                  |
| operating frequency maximum                                                         | 50 1/h                                 |
| degree of pollution                                                                 | 3                                      |
| Voltage                                                                             |                                        |
| insulation voltage rated value                                                      | 690 V                                  |
| surge voltage resistance rated value                                                | 6 kV                                   |
| operating voltage                                                                   |                                        |
| • at AC rated value                                                                 | 690 V                                  |
| operating frequency rated value                                                     |                                        |
| • minimum                                                                           | 50 Hz                                  |
| • maximum                                                                           | 60 Hz                                  |
| Protection class                                                                    |                                        |
| protection class IP                                                                 | IP65                                   |
| degree of protection NEMA rating                                                    | 1, 3R, 4X, 12                          |
| protection class IP on the front                                                    | IP65                                   |
| Dissipation                                                                         |                                        |
| power loss [W] for rated value of the current at AC in hot operating state per pole | 1.1 W                                  |
| Main circuit                                                                        |                                        |
| operational current                                                                 |                                        |
| • at AC-21 at 690 V rated value                                                     | 25 A                                   |
| • at AC-21 A at 240 V rated value                                                   | 25 A                                   |
| • at AC-21 A at 400 V rated value                                                   | 25 A                                   |
| • at AC-21 A at 440 V rated value                                                   | 25 A                                   |

|                                                                                                                 |                      |
|-----------------------------------------------------------------------------------------------------------------|----------------------|
| <ul style="list-style-type: none"> <li>at AC-23 A at 400 V rated value</li> </ul>                               | 20 A                 |
| <b>operating power</b>                                                                                          |                      |
| <ul style="list-style-type: none"> <li>at AC-23 A at 240 V rated value</li> </ul>                               | 5 kW                 |
| <ul style="list-style-type: none"> <li>at AC-23 A at 400 V rated value</li> </ul>                               | 10 kW                |
| <ul style="list-style-type: none"> <li>at AC-23 A at 440 V rated value</li> </ul>                               | 9.5 kW               |
| <ul style="list-style-type: none"> <li>at AC-23 A at 690 V rated value</li> </ul>                               | 10 kW                |
| <ul style="list-style-type: none"> <li>at AC-3 at 240 V rated value</li> </ul>                                  | 4 kW                 |
| <ul style="list-style-type: none"> <li>at AC-3 at 400 V rated value</li> </ul>                                  | 8 kW                 |
| <ul style="list-style-type: none"> <li>at AC-3 at 690 V rated value</li> </ul>                                  | 7.5 kW               |
| <b>Auxiliary circuit</b>                                                                                        |                      |
| number of CO contacts for auxiliary contacts                                                                    | 0                    |
| <b>number of NC contacts for auxiliary contacts</b>                                                             | 1                    |
| <b>number of NO contacts for auxiliary contacts</b>                                                             | 1                    |
| <b>operating voltage of auxiliary contacts at AC maximum</b>                                                    | 500 V                |
| <b>continuous current of the auxiliary contact rated value</b>                                                  | 10 A                 |
| insulation voltage of the auxiliary switch rated value                                                          | 500 V                |
| <b>Suitability</b>                                                                                              |                      |
| <b>suitability for use main switch</b>                                                                          | Yes                  |
| <b>suitability for use switch disconnecter</b>                                                                  | Yes                  |
| <b>suitability for use EMERGENCY OFF switch</b>                                                                 | Yes                  |
| <b>suitability for use safety switch</b>                                                                        | Yes                  |
| <b>suitability for use maintenance/repair switch</b>                                                            | Yes                  |
| <b>Product details</b>                                                                                          |                      |
| product feature can be locked into OFF position                                                                 | Yes                  |
| <b>accessories</b>                                                                                              |                      |
| <b>product extension optional</b>                                                                               |                      |
| <ul style="list-style-type: none"> <li>motor drive</li> </ul>                                                   | No                   |
| <ul style="list-style-type: none"> <li>voltage trigger</li> </ul>                                               | No                   |
| <b>number of connectable NC contacts for auxiliary contacts attachable maximum</b>                              | 2                    |
| <b>number of connectable NO contacts for auxiliary contacts attachable maximum</b>                              | 2                    |
| <b>number of connectable CO contacts for auxiliary contacts attachable maximum</b>                              | 0                    |
| <b>number of bracket locks maximum</b>                                                                          | 3                    |
| <b>hasp thickness of the bracket locks</b>                                                                      | 4 ... 8 mm           |
| <b>Short circuit</b>                                                                                            |                      |
| <b>conditional short-circuit current with line-side fuse protection</b>                                         |                      |
| <ul style="list-style-type: none"> <li>at 690 V by gG fuse rated value</li> </ul>                               | 50 kA                |
| <b>let-through current with closed switch</b>                                                                   |                      |
| <ul style="list-style-type: none"> <li>at 240 V for combination switch + gG fuse maximum</li> </ul>             | 3.5 kA               |
| <ul style="list-style-type: none"> <li>at 440 V for combination switch + gG fuse maximum</li> </ul>             | 3.5 kA               |
| <ul style="list-style-type: none"> <li>at 690 V for combination switch + gG fuse maximum permissible</li> </ul> | 4 kA                 |
| <b>I<sup>2</sup>t value with closed switch</b>                                                                  |                      |
| <ul style="list-style-type: none"> <li>at 240 V for combination switch + gG fuse maximum</li> </ul>             | 4 kA <sup>2</sup> .s |
| <ul style="list-style-type: none"> <li>at 440 V for combination switch + gG fuse maximum</li> </ul>             | 4 kA <sup>2</sup> .s |
| <ul style="list-style-type: none"> <li>at 690 V for combination switch + gG fuse maximum</li> </ul>             | 4 kA <sup>2</sup> .s |
| <b>design of the fuse link</b>                                                                                  |                      |
| <ul style="list-style-type: none"> <li>for short-circuit protection of the main circuit required</li> </ul>     | fuse gL/gG: 25 A     |
| <ul style="list-style-type: none"> <li>for short-circuit protection of the auxiliary switch required</li> </ul> | fuse gL/gG: 10 A     |
| <b>operational current of upstream fuse rated value</b>                                                         | 25 A                 |
| <b>according UL</b>                                                                                             |                      |
| <b>operational current at AC according to UL 508/UL 60947-4-1 rated value</b>                                   | 25 A                 |
| <b>operating voltage at AC at 50/60 Hz according to UL 508/UL 60947-4-1 rated value</b>                         | 600 V                |
| <b>active power [hp] at AC at 480 V according to UL 508/UL 60947-4-1 rated value</b>                            | 10                   |
| <b>active power [hp] at AC at 600 V according to UL 508/UL 60947-4-1 rated value</b>                            | 15                   |
| <b>short-time withstand current (SCCR) at 600 V according to</b>                                                | 5 kA                 |

|                                                                              |                                                                                                                                            |
|------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| <b>UL 508/UL 60947-4-1</b>                                                   |                                                                                                                                            |
| <b>continuous current of upstream fuse according to UL rated value</b>       | 50 A                                                                                                                                       |
| <b>type of fuse according to UL</b>                                          | RK5                                                                                                                                        |
| <b>Connections</b>                                                           |                                                                                                                                            |
| <b>AWG number as coded connectable conductor cross section solid maximum</b> |                                                                                                                                            |
| •                                                                            | 8                                                                                                                                          |
| •                                                                            | 14                                                                                                                                         |
| <b>type of connectable conductor cross-sections for copper conductor</b>     |                                                                                                                                            |
| • solid                                                                      | 1x (1,5...16mm <sup>2</sup> )                                                                                                              |
| • finely stranded with core end processing                                   | 1x (1,5...10mm <sup>2</sup> )                                                                                                              |
| • stranded                                                                   | 1x (1,5...16mm <sup>2</sup> )                                                                                                              |
| <b>type of connectable conductor cross-sections for auxiliary contacts</b>   |                                                                                                                                            |
| • solid                                                                      | lateral auxiliary switch 2x (0,75 ... 2,5mm <sup>2</sup> ), 1x 4mm <sup>2</sup> ; front auxiliary switch 1x (0,75 ... 2,5mm <sup>2</sup> ) |
| • finely stranded with core end processing                                   | lateral auxiliary switch 2x (0,75 ... 1,5mm <sup>2</sup> ), 1x 2,5mm <sup>2</sup> ; front auxiliary switch 1x 2,5mm <sup>2</sup>           |
| • stranded                                                                   | lateral auxiliary switch 2x (0,75 ... 2,5mm <sup>2</sup> ), 1x 4mm <sup>2</sup> ; front auxiliary switch 1x (0,75 ... 2,5mm <sup>2</sup> ) |
| <b>type of electrical connection</b>                                         |                                                                                                                                            |
| • for main current circuit                                                   | box terminal                                                                                                                               |
| • for auxiliary contacts                                                     | connection terminals                                                                                                                       |
| <b>Mechanical Design</b>                                                     |                                                                                                                                            |
| <b>height</b>                                                                | 84 mm                                                                                                                                      |
| <b>width</b>                                                                 | 67 mm                                                                                                                                      |
| <b>depth</b>                                                                 | 92.5 mm                                                                                                                                    |
| <b>type of device</b>                                                        | fixed mounting                                                                                                                             |
| <b>fastening method</b>                                                      | Built-in unit fixed-mounted version                                                                                                        |
| <b>fastening method</b>                                                      |                                                                                                                                            |
| • 4-hole front mounting                                                      | Yes                                                                                                                                        |
| • front mounting with central attachment                                     | No                                                                                                                                         |
| • rail mounting                                                              | No                                                                                                                                         |
| <b>net weight</b>                                                            | 192 g                                                                                                                                      |
| <b>Environmental conditions</b>                                              |                                                                                                                                            |
| <b>ambient temperature during operation</b>                                  |                                                                                                                                            |
| • minimum                                                                    | -25 °C                                                                                                                                     |
| • maximum                                                                    | 55 °C                                                                                                                                      |
| <b>ambient temperature during storage</b>                                    |                                                                                                                                            |
| • minimum                                                                    | -25 °C                                                                                                                                     |
| • maximum                                                                    | 55 °C                                                                                                                                      |
| <b>Approvals Certificates</b>                                                |                                                                                                                                            |
| <b>General Product Approval</b>                                              |                                                                                                                                            |



[Confirmation](#)



|                                 |                          |              |
|---------------------------------|--------------------------|--------------|
| <b>General Product Approval</b> | <b>Marine / Shipping</b> | <b>other</b> |
|---------------------------------|--------------------------|--------------|

[Miscellaneous](#)



[Miscellaneous](#)

|              |                    |
|--------------|--------------------|
| <b>other</b> | <b>Environment</b> |
|--------------|--------------------|

[Confirmation](#)

[Environmental Con-  
firmations](#)

[Environmental Con-  
firmations](#)

## Further information

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD2103-1TP53>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3LD2103-1TP53>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3LD2103-1TP53](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD2103-1TP53)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>





