

No image available for this configuration.

Figure similar

MLFB-Ordering data 1FK7040-5AK71-1PA3

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed (100 K)	6000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	8	Motor type	Compact
Rated torque (100 K)	1.1 Nm	Shaft height	48
Rated current	1.7 A	Cooling	Natural cooling
Static torque (60 K)	1.30 Nm	Radial runout tolerance	0.040 mm
Static torque (100 K)	1.60 Nm	Concentricity tolerance	0.08 mm
Stall current (60 K)	1.80 A	Axial runout tolerance	0.08 mm
Stall current (100 K)	2.25 A	Vibration severity grade	Grade A
Moment of inertia	1.690 kgcm²	Connector size	1
Efficiency	88.0 %	Degree of protection	IP64
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
Torque constant	0.68 Nm/A	Temperature monitoring	KTY84 temperature sensor in the stator winding
Voltage constant at 20° C	43.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
Winding resistance at 20° C	3.30 Ω	Color of the housing	Standard (Anthracite RAL 7016)
Rotating field inductance	17.0 mH	Holding brake	without holding brake
Electrical time constant	5.15 ms	Shaft end	Feather key
Mechanical time constant	3.62 ms	Encoder system	Resolver R14DQ: resolver 14 bits (resolution 16384, internal 2-pole)
Thermal time constant	25 min		
Shaft torsional stiffness	19000 Nm/rad		
Net weight of the motor	3.5 kg		

MLFB-Ordering data 1FK7040-5AK71-1PA3






Optimum operating point		Recommended Motor Module	
Optimum speed	6000 rpm	Rated inverter current	3 A
Optimum power	0.7 kW	Maximum inverter current	6 A
Limiting data		Maximum torque	4.10 Nm
Max. permissible speed (mech.)	9000 rpm		
Max. permissible speed (inverter)	9990 rpm		
Maximum torque	5.1 Nm		
Maximum current	7.7 A		

Confie a titre de secret d'entreprise. Tous droits réservés.
Confidado como secreto industrial. Nos reservamos todos los derechos
Comunicado como segredo empresarial. Reservados todos os direitos


Weitergabe sowie Vervielfältigung dieser Unterlage. Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte vorbehalten, insbesondere fuer den Fall der Patenterteilung oder Gk-Entragung.

The reproduction or use of this document or its contents is not permitted without express written authority. Offenders will be liable for damages. All rights, including rights created by patent grant or registration of a utility model or design, are reserved.

Copyright© Siemens AG 2005
Cada-drawing do not make any manual changes



Connector size 1 = M23;
6-pole for power and brake 10-pole RJ45 socket



Unit	mm [in]	1FK7040-5AK71-1PA3	
Date	2/3/23		
SIEMENS AG			
		DT	