



Figure similar

MLFB-Ordering data 1FK7044-4CH71-1PB0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :




Engineering data		Mechanical data	
Rated speed (100 K)	4500 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	6	Motor type	High Dynamic
Rated torque (100 K)	3.0 Nm	Shaft height	48
Rated current	3.9 A	Cooling	Natural cooling
Static torque (60 K)	3.75 Nm	Radial runout tolerance	0.040 mm
Static torque (100 K)	4.50 Nm	Concentricity tolerance	0.08 mm
Stall current (60 K)	4.35 A	Axial runout tolerance	0.08 mm
Stall current (100 K)	5.40 A	Vibration severity grade	Grade A
Moment of inertia	1.620 kgcm²	Connector size	1
Efficiency	91.0 %	Degree of protection	IP64
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
Torque constant	0.83 Nm/A	Temperature monitoring	Pt1000 temperature sensor
Voltage constant at 20° C	53.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
Winding resistance at 20° C	0.81 Ω	Color of the housing	Standard (Anthracite RAL 7016)
Rotating field inductance	10.2 mH	Holding brake	with holding brake
Electrical time constant	12.50 ms	Shaft end	Feather key
Mechanical time constant	0.44 ms	Encoder system	Resolver R14DQ: resolver 14 bits (resolution 16384, internal 2-pole)
Thermal time constant	45 min		
Shaft torsional stiffness	7900 Nm/rad		
Net weight of the motor	8.0 kg		




Figure similar

MLFB-Ordering data 1FK7044-4CH71-1PB0

Optimum operating point		Recommended Motor Module	
Optimum speed	4500 rpm	Rated inverter current	9 A
Optimum power	1.4 kW	Maximum inverter current	27 A
Limiting data		Maximum torque	13.00 Nm
Max. permissible speed (mech.)	9000 rpm		
Max. permissible speed (inverter)	9000 rpm		
Maximum torque	13.0 Nm		
Maximum current	16.4 A		
Holding brake			
Holding brake version	Permanent-magnet brake		
Holding torque	4.0 Nm		
Power supply voltage	DC 24 V ± 10 %		
Coil current	0.5 A		
Opening time	70 ms		
Closing time	30 ms		
Highest braking work	150 J		



Connector size 1 = M23;
6-pole for power and brake 10-pole RJ45 socket



		
Unit	mm [in]	1FK7044-4CH71-1PB0
Date	7/31/23	
SIEMENS AG		-
-		
		DT