



MLFB-Ordering data1FK7044-7AH71-1KH0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed (100 K)	4500 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	6	Motor type	High Dynamic
Rated torque (100 K)	3.0 Nm	Shaft height	48
Rated current	4.9 A	Cooling	Natural cooling
Static torque (60 K)	3.00 Nm	Radial runout tolerance	0.040 mm
Static torque (100 K)	4.00 Nm	Concentricity tolerance	0.08 mm
Stall current (60 K)	4.60 A	Axial runout tolerance	0.08 mm
Stall current (100 K)	6.30 A	Vibration severity grade	Grade A
Moment of inertia	1.410 kgcm²	Connector size	1
Efficiency	91.0 %	Degree of protection	IP64
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
Torque constant	0.63 Nm/A	Temperature monitoring	KTY84 temperature sensor in the stator winding
Voltage constant at 20° C	42.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
Winding resistance at 20° C	0.81 Ω	Color of the housing	without
Rotating field inductance	11.0 mH	Holding brake	with holding brake
Electrical time constant	13.50 ms	Shaft end	Plain shaft
Mechanical time constant	0.78 ms	Encoder system	Encoder AM16DQ: absolute encoder 16 bits (resolution 65536, encoder-internal 32 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Thermal time constant	45 min		
Shaft torsional stiffness	9500 Nm/rad		
Net weight of the motor	8.3 kg		

MLFB-Ordering data 1FK7044-7AH71-1KH0






Optimum operating point		Recommended Motor Module	
Optimum speed	4500 rpm	Rated inverter current	9 A
Optimum power	1.4 kW	Maximum inverter current	18 A
Limiting data		Maximum torque	11.00 Nm
Max. permissible speed (mech.)	8000 rpm		
Max. permissible speed (inverter)	13300 rpm		
Maximum torque	12.0 Nm		
Maximum current	20.0 A		
Holding brake			
Holding brake version	Permanent-magnet brake		
Holding torque	4.0 Nm		
Power supply voltage	DC 24 V ± 10 %		
Coil current	0.5 A		
Opening time	70 ms		
Closing time	30 ms		
Highest braking work	150 J		

Confie a titre de secret d'entreprise. Tous droits réservés.
Confidado como secreto industrial. Nos reservados todos los derechos
Comunicado como segredo empresarial. Reservados todos os direitos


Weitergabe sowie Vervielfältigung dieser Unterlage. Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte vorbehalten, insbesondere fuer den Fall der Patenterteilung oder Gk-Entragung.

The reproduction or use of this document or its contents is not permitted without express written authority. Offenders will be liable for damages. All rights, including rights created by patent grant or registration of a utility model or design, are reserved.

Copyright© Siemens AG 2005
Cada-drawing do not make any
manual changes



Connector size 1 = M23;
6-pole for power and brake



Unit	mm [in]	1FK7044-7AH71-1KH0	
Date	3/20/23		
SIEMENS AG			
		DT	