

No image available for this configuration.

Figure similar

MLFB-Ordering data 1FK7060-5AF71-1FA2

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data            |                               | Mechanical data          |                                                                                                                                                   |
|-----------------------------|-------------------------------|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated speed (100 K)         | 3000 rpm                      | Motor type               | Permanent-magnet synchronous motor                                                                                                                |
| Number of poles             | 8                             | Motor type               | Compact                                                                                                                                           |
| Rated torque (100 K)        | 4.7 Nm                        | Shaft height             | 63                                                                                                                                                |
| Rated current               | 3.7 A                         | Cooling                  | Natural cooling                                                                                                                                   |
| Static torque (60 K)        | 5.00 Nm                       | Radial runout tolerance  | 0.040 mm                                                                                                                                          |
| Static torque (100 K)       | 6.00 Nm                       | Concentricity tolerance  | 0.10 mm                                                                                                                                           |
| Stall current (60 K)        | 3.70 A                        | Axial runout tolerance   | 0.10 mm                                                                                                                                           |
| Stall current (100 K)       | 4.50 A                        | Vibration severity grade | Grade A                                                                                                                                           |
| Moment of inertia           | 7.950 kgcm²                   | Connector size           | 1                                                                                                                                                 |
| Efficiency                  | 90.0 %                        | Degree of protection     | IP65 and DE flange IP67                                                                                                                           |
| Physical constants          |                               | Design acc. to Code I    | IM B5 (IM V1, IM V3)                                                                                                                              |
| Torque constant             | 1.33 Nm/A                     | Temperature monitoring   | KTY84 temperature sensor in the stator winding                                                                                                    |
| Voltage constant at 20° C   | 84.5 V/1000*min <sup>-1</sup> | Electrical connectors    | Connectors for signals and power rotatable                                                                                                        |
| Winding resistance at 20° C | 1.44 Ω                        | Color of the housing     | without                                                                                                                                           |
| Rotating field inductance   | 14.7 mH                       | Holding brake            | without holding brake                                                                                                                             |
| Electrical time constant    | 10.20 ms                      | Shaft end                | Feather key                                                                                                                                       |
| Mechanical time constant    | 1.94 ms                       | Encoder system           | Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions) |
| Thermal time constant       | 30 min                        |                          |                                                                                                                                                   |
| Shaft torsional stiffness   | 42000 Nm/rad                  |                          |                                                                                                                                                   |
| Net weight of the motor     | 7.0 kg                        |                          |                                                                                                                                                   |

MLFB-Ordering data                      1FK7060-5AF71-1FA2





| Optimum operating point           |          | Recommended Motor Module |          |
|-----------------------------------|----------|--------------------------|----------|
| Optimum speed                     | 3000 rpm | Rated inverter current   | 5 A      |
| Optimum power                     | 1.5 kW   | Maximum inverter current | 10 A     |
| Limiting data                     |          | Maximum torque           | 13.20 Nm |
| Max. permissible speed (mech.)    | 7200 rpm |                          |          |
| Max. permissible speed (inverter) | 6800 rpm |                          |          |
| Maximum torque                    | 18.0 Nm  |                          |          |
| Maximum current                   | 15.0 A   |                          |          |

Confie a titre de secret d'entreprise. Tous droits réservés.  
Confidado como secreto industrial. Nos reservamos todos los derechos  
Comunicado como segredo empresarial. Reservados todos os direitos



Weitergabe sowie Vervielfältigung dieser Unterlage. Verwer-  
tung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht  
ausdrücklich zugestanden. Zuwahlungen verpflichten  
zu Schadenersatz. Alle Rechte vorbehalten, insbesondere für  
den Fall der Patenterteilung oder der Eintragung

The reproduction or use of this document or its  
contents is not permitted without express written authority.  
Defenders will be liable for damages. All rights, including rights  
created by patent grant or registration of a utility model or design,  
are reserved.

Copyright© Siemens AG 2005  
Cada-drawing do not make any  
manual changes



Connector size 1 = M23;  
6-pole for power and brake 10-pole RJ45 socket



|            |         |                     |
|------------|---------|---------------------|
|            | -       |                     |
|            | -       |                     |
| Unit       | mm [in] | 1FK7060-5AF 71-1FA2 |
| Date       | 3/29/23 |                     |
| SIEMENS AG |         | -                   |
| -          |         | DT                  |