


MLFB-Ordering data1FK7063-5AF71-1AA0



Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data            |                               | Mechanical data          |                                                                                  |
|-----------------------------|-------------------------------|--------------------------|----------------------------------------------------------------------------------|
| Rated speed (100 K)         | 3000 rpm                      | Motor type               | Permanent-magnet synchronous motor                                               |
| Number of poles             | 8                             | Motor type               | Compact                                                                          |
| Rated torque (100 K)        | 7.3 Nm                        | Shaft height             | 63                                                                               |
| Rated current               | 5.6 A                         | Cooling                  | Natural cooling                                                                  |
| Static torque (60 K)        | 9.10 Nm                       | Radial runout tolerance  | 0.040 mm                                                                         |
| Static torque (100 K)       | 11.00 Nm                      | Concentricity tolerance  | 0.10 mm                                                                          |
| Stall current (60 K)        | 6.60 A                        | Axial runout tolerance   | 0.10 mm                                                                          |
| Stall current (100 K)       | 8.00 A                        | Vibration severity grade | Grade A                                                                          |
| Moment of inertia           | 15.100 kgcm²                  | Connector size           | 1                                                                                |
| Efficiency                  | 91.0 %                        | Degree of protection     | IP64                                                                             |
| Physical constants          |                               | Design acc. to Code I    | IM B5 (IM V1, IM V3)                                                             |
| Torque constant             | 1.37 Nm/A                     | Temperature monitoring   | KTY84 temperature sensor in the stator winding                                   |
| Voltage constant at 20° C   | 87.5 V/1000*min <sup>-1</sup> | Electrical connectors    | Connectors for signals and power rotatable                                       |
| Winding resistance at 20° C | 0.65 Ω                        | Color of the housing     | without                                                                          |
| Rotating field inductance   | 7.7 mH                        | Holding brake            | without holding brake                                                            |
| Electrical time constant    | 11.80 ms                      | Shaft end                | Feather key                                                                      |
| Mechanical time constant    | 1.56 ms                       | Encoder system           | Encoder IC2048S/R: incremental encoder sin/cos 1 Vpp 2048 S/R with C and D track |
| Thermal time constant       | 40 min                        |                          |                                                                                  |
| Shaft torsional stiffness   | 35000 Nm/rad                  |                          |                                                                                  |
| Net weight of the motor     | 11.5 kg                       |                          |                                                                                  |

MLFB-Ordering data                      1FK7063-5AF71-1AA0






| Optimum operating point           |          | Recommended Motor Module |          |
|-----------------------------------|----------|--------------------------|----------|
| Optimum speed                     | 3000 rpm | Rated inverter current   | 9 A      |
| Optimum power                     | 2.3 kW   | Maximum inverter current | 18 A     |
| Limiting data                     |          | Maximum torque           | 24.50 Nm |
| Max. permissible speed (mech.)    | 7200 rpm |                          |          |
| Max. permissible speed (inverter) | 6600 rpm |                          |          |
| Maximum torque                    | 35.0 Nm  |                          |          |
| Maximum current                   | 28.0 A   |                          |          |

Confie a titre de secret d'entreprise. Tous droits réservés.  
Confidado como secreto industrial. Nos reservamos todos los derechos  
Comunicado como segredo empresarial. Reservados todos os direitos


Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte vorbehalten, insbesondere für den Fall der Patenterteilung oder der Eintragung.

The reproduction or use of this document or its contents is not permitted without express written authority. Offenders will be liable for damages. All rights, including rights created by patent grant or registration of a utility model or design, are reserved.

Copyright© Siemens AG 2005  
Cada-drawing do not make any  
manual changes



Connector size 1 = M23;  
6-pole for power and brake



Connector size M23, 17-pole

|            |         |                     |
|------------|---------|---------------------|
|            | -       |                     |
|            | -       |                     |
| Unit       | mm [in] | 1FK7063-5AF 71-1AA0 |
| Date       | 2/8/23  |                     |
| SIEMENS AG |         | -                   |
| -          |         | DT                  |