




MLFB-Ordering data 1FK7064-7AF71-1FG5

Client order no. :	Item no. :
Order no. :	Consignment no. :
Offer no. :	Project :
Remarks :	


Engineering data		Mechanical data	
Rated speed (100 K)	3000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	6	Motor type	High Dynamic
Rated torque (100 K)	8.0 Nm	Shaft height	63
Rated current	7.5 A	Cooling	Natural cooling
Static torque (60 K)	9.00 Nm	Radial runout tolerance	0.040 mm
Static torque (100 K)	12.00 Nm	Concentricity tolerance	0.10 mm
Stall current (60 K)	8.50 A	Axial runout tolerance	0.10 mm
Stall current (100 K)	11.00 A	Vibration severity grade	Grade A
Moment of inertia	6.500 kgcm²	Connector size	1
Efficiency	93.0 %	Degree of protection	IP65 and DE flange IP67
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
Torque constant	1.03 Nm/A	Temperature monitoring	KTY84 temperature sensor in the stator winding
Voltage constant at 20° C	68.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
Winding resistance at 20° C	0.35 Ω	Color of the housing	Standard (Anthracite RAL 7016)
Rotating field inductance	10.7 mH	Holding brake	without holding brake
Electrical time constant	30.50 ms	Shaft end	Plain shaft
Mechanical time constant	0.64 ms	Encoder system	Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Thermal time constant	55 min		
Shaft torsional stiffness	30000 Nm/rad		
Net weight of the motor	15.5 kg		

MLFB-Ordering data 1FK7064-7AF71-1FG5

Optimum operating point		Recommended Motor Module	
Optimum speed	3000 rpm	Rated inverter current	18 A
Optimum power	2.5 kW	Maximum inverter current	36 A
Limiting data		Maximum torque	32.00 Nm
Max. permissible speed (mech.)	6000 rpm		
Max. permissible speed (inverter)	8500 rpm		
Maximum torque	32.0 Nm		
Maximum current	31.0 A		



Connector size 1 = M23;
6-pole for power and brake 10-pole RJ45 socket



		- -
Unit	mm (in)	1FK7064-7AF71-1FG5
Date	6/19/23	
SIEMENS AG		-
-		DT