

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7080-2AH71-1CA1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data	
Rated speed (100 K)	4500 rpm
Number of poles	8
Rated torque (100 K)	4.5 Nm
Rated current	4.8 A
Static torque (60 K)	6.60 Nm
Static torque (100 K)	8.00 Nm
Stall current (60 K)	6.00 A
Stall current (100 K)	7.40 A
Moment of inertia	14.200 kgcm²
Efficiency	92.0 %
Physical constants	
Torque constant	1.08 Nm/A
Voltage constant at 20° C	68.5 V/1000*min ⁻¹
Winding resistance at 20° C	0.42 Ω
Rotating field inductance	7.3 mH
Electrical time constant	17.30 ms
Mechanical time constant	1.54 ms
Thermal time constant	40 min
Shaft torsional stiffness	120000 Nm/rad
Net weight of the motor	10.3 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	80
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft end	Feather key
Encoder system	Encoder AM24DQI: absolute encoder 24 bits (resolution 16777216, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)



Figure similar

MLFB-Ordering data 1FK7080-2AH71-1CA1






Optimum operating point		Recommended Motor Module	
Optimum speed	4000 rpm	Rated inverter current	9 A
Optimum power	2.4 kW	Maximum inverter current	27 A
Limiting data		Maximum torque	24.70 Nm
Max. permissible speed (mech.)	6000 rpm		
Max. permissible speed (inverter)	6000 rpm		
Maximum torque	25.0 Nm		
Maximum current	27.5 A		

Copyright© Siemens AG 2005
Cable drawing do not make any manual changes


The reproduction or use of this document or its contents is not permitted without express written authority. Offenders will be liable for damages. All rights, including rights created by patent grant or registration of a utility model or design, are reserved.

Weitergabe sowie Vervielfältigung dieser Unterlage, Vervielfältigung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte vorbehalten, insbesondere fuer den Fall der Patenterteilung oder GK-Entragung.

Confie a titre de secret d'entreprise. Tous droits reserves. Confido como secreto industrial. Nos reservamos todos los derechos. Comunicado como segredo empresarial. Reservados todos os direitos.



Connector size 1 = M23;
6-pole for power and brake



Unit	mm [in]	1FK7080-2AH71-1CA1	
Date	8/1/23		
SIEMENS AG			
		DT	