


MLFB-Ordering data1FK7080-5AF71-1AG3



Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data            |                                | Mechanical data          |                                                                                  |
|-----------------------------|--------------------------------|--------------------------|----------------------------------------------------------------------------------|
| Rated speed (100 K)         | 3000 rpm                       | Motor type               | Permanent-magnet synchronous motor                                               |
| Number of poles             | 8                              | Motor type               | Compact                                                                          |
| Rated torque (100 K)        | 6.8 Nm                         | Shaft height             | 80                                                                               |
| Rated current               | 4.4 A                          | Cooling                  | Natural cooling                                                                  |
| Static torque (60 K)        | 6.60 Nm                        | Radial runout tolerance  | 0.050 mm                                                                         |
| Static torque (100 K)       | 8.00 Nm                        | Concentricity tolerance  | 0.10 mm                                                                          |
| Stall current (60 K)        | 4.00 A                         | Axial runout tolerance   | 0.10 mm                                                                          |
| Stall current (100 K)       | 4.80 A                         | Vibration severity grade | Grade A                                                                          |
| Moment of inertia           | 15.000 kgcm²                   | Connector size           | 1                                                                                |
| Efficiency                  | 92.0 %                         | Degree of protection     | IP64                                                                             |
| Physical constants          |                                | Design acc. to Code I    | IM B5 (IM V1, IM V3)                                                             |
| Torque constant             | 1.61 Nm/A                      | Temperature monitoring   | KTY84 temperature sensor in the stator winding                                   |
| Voltage constant at 20° C   | 102.5 V/1000*min <sup>-1</sup> | Electrical connectors    | Connectors for signals and power rotatable                                       |
| Winding resistance at 20° C | 1.04 Ω                         | Color of the housing     | Standard (Anthracite RAL 7016)                                                   |
| Rotating field inductance   | 14.0 mH                        | Holding brake            | without holding brake                                                            |
| Electrical time constant    | 13.50 ms                       | Shaft end                | Plain shaft                                                                      |
| Mechanical time constant    | 1.78 ms                        | Encoder system           | Encoder IC2048S/R: incremental encoder sin/cos 1 Vpp 2048 S/R with C and D track |
| Thermal time constant       | 40 min                         |                          |                                                                                  |
| Shaft torsional stiffness   | 126000 Nm/rad                  |                          |                                                                                  |
| Net weight of the motor     | 10.0 kg                        |                          |                                                                                  |

MLFB-Ordering data                      1FK7080-5AF71-1AG3




| Optimum operating point           |          | Recommended Motor Module |          |
|-----------------------------------|----------|--------------------------|----------|
| Optimum speed                     | 3000 rpm | Rated inverter current   | 5 A      |
| Optimum power                     | 2.1 kW   | Maximum inverter current | 10 A     |
| Limiting data                     |          | Maximum torque           | 16.60 Nm |
| Max. permissible speed (mech.)    | 6000 rpm |                          |          |
| Max. permissible speed (inverter) | 5600 rpm |                          |          |
| Maximum torque                    | 25.0 Nm  |                          |          |
| Maximum current                   | 18.0 A   |                          |          |

Copyright© Siemens AG 2005  
Cod-drawing do not make any manual changes


The reproduction or use of this document or its contents is not permitted without express written authority. Offenders will be liable for damages. All rights, including rights created by patent grant or registration of a utility model or design, are reserved.

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte vorbehalten, insbesondere fuer den Fall der Patenterteilung oder GK-Entragung.

Confide a titre de secret d'entreprise. Tous droits reserves. Confido como secreto Industrial. Nos reservamos todos los derechos Comunicado como segredo empresarial. Reservados todos os direitos





DIN 332-DR M12



Connector size 1 = M23;  
6-pole for power and brake

Connector size M23, 17-pole



|                                                                                       |      |         |                     |
|---------------------------------------------------------------------------------------|------|---------|---------------------|
|  | Unit | mm [in] | 1FK7080-5AF 71-1AG3 |
|                                                                                       | Date | 6/12/23 |                     |
| SIEMENS AG                                                                            |      | -       |                     |
| -                                                                                     |      | DT      |                     |