

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data 1FK7085-4CC71-1CA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed (100 K)	2000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	8	Motor type	High Dynamic
Rated torque (100 K)	15.0 Nm	Shaft height	80
Rated current	10.0 A	Cooling	Natural cooling
Static torque (60 K)	18.30 Nm	Radial runout tolerance	0.050 mm
Static torque (100 K)	22.00 Nm	Concentricity tolerance	0.10 mm
Stall current (60 K)	10.90 A	Axial runout tolerance	0.10 mm
Stall current (100 K)	13.50 A	Vibration severity grade	Grade A
Moment of inertia	22.000 kgcm ²	Connector size	1
Efficiency	92.0 %	Degree of protection	IP64
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
Torque constant	1.63 Nm/A	Temperature monitoring	Pt1000 temperature sensor
Voltage constant at 20° C	105.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
Winding resistance at 20° C	0.31 Ω	Color of the housing	Standard (Anthracite RAL 7016)
Rotating field inductance	9.8 mH	Holding brake	without holding brake
Electrical time constant	31.50 ms	Shaft end	Feather key
Mechanical time constant	0.77 ms	Encoder system	Encoder AM24DQI: absolute encoder 24 bits (resolution 16777216, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Thermal time constant	45 min		
Shaft torsional stiffness	84000 Nm/rad		
Net weight of the motor	23.0 kg		



MLFB-Ordering data 1FK7085-4CC71-1CA0




Optimum operating point		Recommended Motor Module	
Optimum speed	2000 rpm	Rated inverter current	18 A
Optimum power	3.1 kW	Maximum inverter current	54 A
Limiting data		Maximum torque	65.00 Nm
Max. permissible speed (mech.)	6000 rpm		
Max. permissible speed (inverter)	5500 rpm		
Maximum torque	65.0 Nm		
Maximum current	51.0 A		

Confie a titre de secret d'entreprise. Tous droits réservés.
Confidado como secreto industrial. Nos reservamos todos los derechos
Comunicado como segredo empresarial. Reservados todos os direitos


Weitergabe sowie Vervielfältigung dieser Unterlage. Verwer-
tung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht
ausdrücklich zugestanden. Zuwiderhandlungen verpflichten
zu Schadenersatz. Alle Rechte vorbehalten, insbesondere fuer
den Fall der Patenterteilung oder GK-Entragung.

The reproduction or use of this document or its
contents is not permitted without express written authority.
Offenders will be liable for damages. All rights, including rights
created by patent grant or registration of a utility model or design,
are reserved.



Copyright© Siemens AG 2005
Cada-drawing do not make any
manual changes



DIN 332-DR M12



Connector size 1 = M23;
6-pole for power and brake



Unit	mm [in]	1FK7085-4CC71-1CA0	
Date	8/1/23		
SIEMENS AG			
		DT	