

MLFB-Ordering data1FK7086-7AF71-1EH3



Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data            |                               | Mechanical data          |                                                                                                 |
|-----------------------------|-------------------------------|--------------------------|-------------------------------------------------------------------------------------------------|
| Rated speed (100 K)         | 3000 rpm                      | Motor type               | Permanent-magnet synchronous motor                                                              |
| Number of poles             | 8                             | Motor type               | High Dynamic                                                                                    |
| Rated torque (100 K)        | 6.5 Nm                        | Shaft height             | 80                                                                                              |
| Rated current               | 5.5 A                         | Cooling                  | Natural cooling                                                                                 |
| Static torque (60 K)        | 23.50 Nm                      | Radial runout tolerance  | 0.050 mm                                                                                        |
| Static torque (100 K)       | 28.00 Nm                      | Concentricity tolerance  | 0.10 mm                                                                                         |
| Stall current (60 K)        | 17.00 A                       | Axial runout tolerance   | 0.10 mm                                                                                         |
| Stall current (100 K)       | 21.00 A                       | Vibration severity grade | Grade A                                                                                         |
| Moment of inertia           | 25.000 kgcm²                  | Connector size           | 1.5                                                                                             |
| Efficiency                  | 93.0 %                        | Degree of protection     | IP64                                                                                            |
| Physical constants          |                               | Design acc. to Code I    | IM B5 (IM V1, IM V3)                                                                            |
| Torque constant             | 1.33 Nm/A                     | Temperature monitoring   | KTY84 temperature sensor in the stator winding                                                  |
| Voltage constant at 20° C   | 85.0 V/1000*min <sup>-1</sup> | Electrical connectors    | Connectors for signals and power rotatable                                                      |
| Winding resistance at 20° C | 0.12 Ω                        | Color of the housing     | Standard (Anthracite RAL 7016)                                                                  |
| Rotating field inductance   | 3.0 mH                        | Holding brake            | with holding brake                                                                              |
| Electrical time constant    | 25.00 ms                      | Shaft end                | Plain shaft                                                                                     |
| Mechanical time constant    | 0.47 ms                       | Encoder system           | Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface |
| Thermal time constant       | 65 min                        |                          |                                                                                                 |
| Shaft torsional stiffness   | 83000 Nm/rad                  |                          |                                                                                                 |
| Net weight of the motor     | 25.7 kg                       |                          |                                                                                                 |

MLFB-Ordering data                      1FK7086-7AF71-1EH3






| Optimum operating point           |                        | Recommended Motor Module |          |
|-----------------------------------|------------------------|--------------------------|----------|
| Optimum speed                     | 2000 rpm               | Rated inverter current   | 30 A     |
| Optimum power                     | 3.8 kW                 | Maximum inverter current | 56 A     |
| Limiting data                     |                        | Maximum torque           | 72.00 Nm |
| Max. permissible speed (mech.)    | 6000 rpm               |                          |          |
| Max. permissible speed (inverter) | 6800 rpm               |                          |          |
| Maximum torque                    | 105.0 Nm               |                          |          |
| Maximum current                   | 112.0 A                |                          |          |
| Holding brake                     |                        |                          |          |
| Holding brake version             | Permanent-magnet brake |                          |          |
| Holding torque                    | 22.0 Nm                |                          |          |
| Power supply voltage              | DC 24 V ± 10 %         |                          |          |
| Coil current                      | 0.9 A                  |                          |          |
| Opening time                      | 200 ms                 |                          |          |
| Closing time                      | 60 ms                  |                          |          |
| Highest braking work              | 1400 J                 |                          |          |

Confie a titre de secret d'entreprise. Tous droits réservés.  
Confidado como secreto industrial. Nos reservamos todos los derechos  
Comunicado como segredo empresarial. Reservados todos os direitos


Weitergabe sowie Vervielfältigung dieser Unterlage. Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte vorbehalten, insbesondere fuer den Fall der Patenterteilung oder GK-Entragung.

The reproduction or use of this document or its contents is not permitted without express written authority. Offenders will be liable for damages. All rights, including rights created by patent grant or registration of a utility model or design, are reserved.

Copyright© Siemens AG 2005  
Cada-drawing do not make any  
manual changes



Connector size 1.5 = M40;  
6-pole for power and brake



Connector size M23, 17-pole

|            |         |                    |
|------------|---------|--------------------|
|            | -       |                    |
|            | -       |                    |
| Unit       | mm [in] | 1FK7086-7AF71-1EH3 |
| Date       | 2/15/23 |                    |
| SIEMENS AG |         | -                  |
| -          |         | DT                 |