

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data                      1FK7101-2AF71-1QG2

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :






| Engineering data            |                               | Mechanical data          |                                                       |
|-----------------------------|-------------------------------|--------------------------|-------------------------------------------------------|
| Rated speed (100 K)         | 3000 rpm                      | Motor type               | Permanent-magnet synchronous motor                    |
| Number of poles             | 8                             | Motor type               | Compact                                               |
| Rated torque (100 K)        | 15.5 Nm                       | Shaft height             | 100                                                   |
| Rated current               | 11.6 A                        | Cooling                  | Natural cooling                                       |
| Static torque (60 K)        | 22.50 Nm                      | Radial runout tolerance  | 0.050 mm                                              |
| Static torque (100 K)       | 27.00 Nm                      | Concentricity tolerance  | 0.10 mm                                               |
| Stall current (60 K)        | 15.20 A                       | Axial runout tolerance   | 0.10 mm                                               |
| Stall current (100 K)       | 18.80 A                       | Vibration severity grade | Grade A                                               |
| Moment of inertia           | 79.000 kgcm²                  | Connector size           | 1.5                                                   |
| Efficiency                  | 93.0 %                        | Degree of protection     | IP65 and DE flange IP67                               |
| Physical constants          |                               | Design acc. to Code I    | IM B5 (IM V1, IM V3)                                  |
| Torque constant             | 1.44 Nm/A                     | Temperature monitoring   | Pt1000 temperature sensor                             |
| Voltage constant at 20° C   | 92.5 V/1000*min <sup>-1</sup> | Electrical connectors    | Connectors for signals and power rotatable            |
| Winding resistance at 20° C | 0.14 Ω                        | Color of the housing     | Standard (Anthracite RAL 7016)                        |
| Rotating field inductance   | 3.5 mH                        | Holding brake            | without holding brake                                 |
| Electrical time constant    | 25.00 ms                      | Shaft end                | Plain shaft                                           |
| Mechanical time constant    | 1.62 ms                       | Encoder system           | Encoder AS20DQI: absolute encoder single-turn 20 bits |
| Thermal time constant       | 60 min                        |                          |                                                       |
| Shaft torsional stiffness   | 164000 Nm/rad                 |                          |                                                       |
| Net weight of the motor     | 23.0 kg                       |                          |                                                       |




Figure similar

MLFB-Ordering data                    1FK7101-2AF71-1QG2

| Optimum operating point           |          | Recommended Motor Module |          |
|-----------------------------------|----------|--------------------------|----------|
| Optimum speed                     | 3000 rpm | Rated inverter current   | 18 A     |
| Optimum power                     | 4.8 kW   | Maximum inverter current | 54 A     |
| Limiting data                     |          | Maximum torque           | 72.00 Nm |
| Max. permissible speed (mech.)    | 5000 rpm |                          |          |
| Max. permissible speed (inverter) | 5000 rpm |                          |          |
| Maximum torque                    | 80.0 Nm  |                          |          |
| Maximum current                   | 63.0 A   |                          |          |



Connector size 1.5 = M40;  
6-pole for power and brake



10-pole RJ45 socket

|            |         |                    |
|------------|---------|--------------------|
|            | -       |                    |
|            | -       |                    |
| Unit       | mm [in] | 1FK7101-2AF71-1QG2 |
| Date       | 2/8/23  |                    |
| SIEMENS AG |         | -                  |
| -          |         | DT                 |

Copyright© Siemens AG 2005  
The reproduction or use of this document or its contents is not permitted without express written authority. Diffenders will be liable for damages. All rights, including rights created by patent grant or registration of a utility model or design, are reserved.  
Weitergabe sowie Vervielfältigung dieser Unterlage, Vervielfältigung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte vorbehalten, insbesondere fuer den Fall der Patenterteilung oder Gk-Entragung.  
Confide a titre de secret d'entreprise. Tous droits reserves. Confido como secreto industrial. Nos reservamos todos los derechos Comunicado como segredo empresarial. Reservados todos os direitos