

Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data 1FK7105-5AC71-1AA2



Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data            |                                | Mechanical data          |                                                                                  |
|-----------------------------|--------------------------------|--------------------------|----------------------------------------------------------------------------------|
| Rated speed (100 K)         | 2000 rpm                       | Motor type               | Permanent-magnet synchronous motor                                               |
| Number of poles             | 8                              | Motor type               | Compact                                                                          |
| Rated torque (100 K)        | 37.0 Nm                        | Shaft height             | 100                                                                              |
| Rated current               | 16.0 A                         | Cooling                  | Natural cooling                                                                  |
| Static torque (60 K)        | 40.00 Nm                       | Radial runout tolerance  | 0.050 mm                                                                         |
| Static torque (100 K)       | 48.00 Nm                       | Concentricity tolerance  | 0.10 mm                                                                          |
| Stall current (60 K)        | 17.00 A                        | Axial runout tolerance   | 0.10 mm                                                                          |
| Stall current (100 K)       | 20.00 A                        | Vibration severity grade | Grade A                                                                          |
| Moment of inertia           | 156.000 kgcm²                  | Connector size           | 1.5                                                                              |
| Efficiency                  | 93.0 %                         | Degree of protection     | IP65 and DE flange IP67                                                          |
| Physical constants          |                                | Design acc. to Code I    | IM B5 (IM V1, IM V3)                                                             |
| Torque constant             | 2.37 Nm/A                      | Temperature monitoring   | KTY84 temperature sensor in the stator winding                                   |
| Voltage constant at 20° C   | 151.0 V/1000*min <sup>-1</sup> | Electrical connectors    | Connectors for signals and power rotatable                                       |
| Winding resistance at 20° C | 0.17 Ω                         | Color of the housing     | without                                                                          |
| Rotating field inductance   | 4.4 mH                         | Holding brake            | without holding brake                                                            |
| Electrical time constant    | 26.00 ms                       | Shaft end                | Feather key                                                                      |
| Mechanical time constant    | 1.40 ms                        | Encoder system           | Encoder IC2048S/R: incremental encoder sin/cos 1 Vpp 2048 S/R with C and D track |
| Thermal time constant       | 70 min                         |                          |                                                                                  |
| Shaft torsional stiffness   | 125000 Nm/rad                  |                          |                                                                                  |
| Net weight of the motor     | 39.1 kg                        |                          |                                                                                  |

MLFB-Ordering data                      1FK7105-5AC71-1AA2




| Optimum operating point           |          | Recommended Motor Module |           |
|-----------------------------------|----------|--------------------------|-----------|
| Optimum speed                     | 2000 rpm | Rated inverter current   | 30 A      |
| Optimum power                     | 7.8 kW   | Maximum inverter current | 56 A      |
| Limiting data                     |          | Maximum torque           | 127.00 Nm |
| Max. permissible speed (mech.)    | 5000 rpm |                          |           |
| Max. permissible speed (inverter) | 3800 rpm |                          |           |
| Maximum torque                    | 150.0 Nm |                          |           |
| Maximum current                   | 72.0 A   |                          |           |

Copyright© Siemens AG 2005  
Cod-drawing do not make any  
manual changes


The reproduction or use of this document or its  
contents is not permitted without express written authority.  
Diffenders will be liable for damages. All rights, including rights  
created by patent grant or registration of a utility model or design,  
are reserved.

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwer-  
tung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht  
ausdrücklich zugestanden. Zuwahlhandlungen verpflichten  
zu Schadenersatz. Alle Rechte vorbehalten, insbesondere fuer  
den Fall der Patenterteilung oder Gk-Entragung.


Confide a titre de secret d'entreprise. Tous droits reserves.  
Confido como secreto industrial. Nos reservamos todos los derechos  
Comunicado como segredo empresarial. Reservados todos os direitos




DIN 332-DR M12



Connector size 1.5 = M40;  
6-pole for power and brake



Connector size M23, 17-pole



|            |      |         |                    |
|------------|------|---------|--------------------|
|            | Unit | mm [in] | 1FK7105-5AC71-1AA2 |
|            | Date | 7/28/23 |                    |
| SIEMENS AG |      | -       |                    |
| -          |      | DT      |                    |