



Figure similar

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7086-5AF71-1DG0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data        |                         |
|-------------------------|-------------------------|
| Rated speed             | 3,000 rpm               |
| Number of poles         | 10                      |
| Rated torque (100 K)    | 18.0 Nm                 |
| Rated current           | 11.00 A                 |
| Static torque (60 K)    | 23.0 Nm                 |
| Static torque (100 K)   | 28.0 Nm                 |
| Stall current (60 K)    | 12.90 A                 |
| Stall current (100 K)   | 15.50 A                 |
| Rotor moment of inertia | 63.60 kgcm <sup>2</sup> |
| Efficiency              | 93.0 %                  |

| Physical constants          |                                |
|-----------------------------|--------------------------------|
| Torque constant             | 1.78 Nm/A                      |
| Voltage constant at 20° C   | 113.5 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 0.23 Ω                         |
| Rotary field inductance     | 4.0 mH                         |
| Electrical time constant    | 17.00 ms                       |
| Mechanical time constant    | 1.40 ms                        |
| Thermal time constant       | 60 min                         |
| Shaft torsional stiffness   | 74,000 Nm/rad                  |
| Net weight of the motor     | 27.5 kg                        |

| Mechanical data          |                                                                                                                            |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Motor type               | Permanent-magnet synchronous motor                                                                                         |
| Motor type               | Compact                                                                                                                    |
| Shaft height             | 80                                                                                                                         |
| Cooling                  | Natural cooling                                                                                                            |
| Radial runout tolerance  | 0.050 mm                                                                                                                   |
| Concentricity tolerance  | 0.100 mm                                                                                                                   |
| Axial runout tolerance   | 0.100 mm                                                                                                                   |
| Vibration severity grade | Grade A                                                                                                                    |
| Degree of protection     | IP64                                                                                                                       |
| Design acc. to Code I    | IM B5 (compatible with 1FT6)                                                                                               |
| Temperature monitoring   | Pt1000 temperature sensor                                                                                                  |
| Color of the housing     | Standard (pearl dark gray similar to RAL 9023)                                                                             |
| Shaft end type           | Plain shaft                                                                                                                |
| Sensor design            | Encoder IC22DQ: incremental encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + commutation position 11 bits |
| Electrical connection    | Connector turnable                                                                                                         |
| Connector size           | 1.5                                                                                                                        |

| Optimum operating point |           |
|-------------------------|-----------|
| Optimum speed           | 3,000 rpm |
| Optimum power           | 5.7 kW    |

| Limiting data                     |           |
|-----------------------------------|-----------|
| Max. permissible speed (mech.)    | 8,000 rpm |
| Max. permissible speed (inverter) | 5,100 rpm |
| Maximum torque                    | 120.0 Nm  |
| Maximum current                   | 78.00 A   |

| Recommended Motor Module |         |
|--------------------------|---------|
| Rated inverter current   | 18.00 A |
| Maximum inverter current | 54.00 A |
| Maximum torque           | 86.0 Nm |