

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7132-5SF71-5CA0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed	3,000 rpm
Number of poles	8
Rated torque (100 K)	113.0 Nm
Rated current	69.00 A
Static torque (60 K)	120.0 Nm
Static torque (100 K)	140.0 Nm
Stall current (60 K)	72.00 A
Stall current (100 K)	85.00 A
Rotor moment of inertia	459.00 kgcm ²
Efficiency	95.0 %

Physical constants	
Torque constant	1.69 Nm/A
Voltage constant at 20° C	116.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.04 Ω
Rotary field inductance	1.2 mH
Electrical time constant	28.00 ms
Mechanical time constant	2.10 ms
Thermal time constant	20 min
Shaft torsional stiffness	347,000 Nm/rad
Net weight of the motor	81.0 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	132
Cooling	Forced ventilation
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.125 mm
Axial runout tolerance	0.125 mm
Vibration severity grade	Grade A
Degree of protection	IP64
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Shaft end type	Fitted key and keyway
Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Electrical connection	Terminal box transverse right

Optimum operating point	
Optimum speed	3,000 rpm
Optimum power	35.5 kW

Limiting data	
Max. permissible speed (mech.)	3,600 rpm
Max. permissible speed (inverter)	3,600 rpm
Maximum torque	305.0 Nm
Maximum current	210.00 A

Recommended Motor Module	
Rated inverter current	85.00 A
Maximum inverter current	141.00 A
Maximum torque	220.0 Nm