

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2112B

SIMOTICS SD - 112 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area																	
Electrical data																	
U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	4.00	-/-	8.20	1460	26.0	86.6	87.3	86.4	0.81	0.74	0.61	7.1	2.5	3.2	IE2
690	Y	50	4.00	-/-	4.75	1460	26.0	86.6	87.3	86.4	0.81	0.74	0.61	7.1	2.5	3.2	IE2
460	Δ	60	4.55	-/-	8.00	1760	24.5	87.5	88.0	86.9	0.82	0.76	0.63	7.5	2.4	3.2	IE2
460	Δ	60	3.70	-/-	6.90	1770	20.0	87.5	87.2	85.1	0.77	0.69	0.56	8.7	3.0	4.0	IE2
IM B5 / IM 3001			FS 112 M			IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 8.8 s 14.4 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	58 / 70 dB(A) ^{2) 3)}	62 / 74 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0140 kg m ²		Thermal class	F
Bearing DE NDE	6306 2Z C3	6306 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	46 kg
Grease nipple	-/-		Coating (paint finish)	Special paint finish C3
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 F01	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
IN LVM		SPC			
SIEMENS	document type				document status
	datasheet				released
	title				document number
	1LE1601-1BB23-4FB4				
© INNOMOTICS 2023		rev.	creation date	language	Page
		951	2023-12-18	en	1/1