



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8083-1HF02-2GA2

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	3.3	18.0	7.5	398	61.7	1,750	34	18.0	10,000	21.0	8	0.831	0.800	3.8
	BLM/SLM 400V	2.8	18.0	7.5	346	53.3	1,500	34	18.0	10,000	21.0	8	0.809	0.800	3.8
	ALM/BLM/SLM 480V	3.7	18.0	7.6	447	70.0	2,000	34	18.0	10,000	21.0	8	0.850	0.790	3.7

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	80
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	10 min
Moment of inertia	64 kgcm²
Weight (approx.)	32 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk803

Cooling data and sound pressure level

Airflow, min.	0.02 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	95 Pa

External fan

Max. power consumption

1 AC 230 V / 50 Hz (±10%)	0.20 A
1 AC 230 V / 60 Hz (±10%)	0.16 A
1 AC 265 V / 60 Hz (±10%)	0.19 A

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm


Copyright© Siemens AG 2005
Cod-drawing do not make any manual changes

The reproduction or use of this document or its contents is not permitted without express written authority. Diffenders will be liable for damages. All rights, including rights created by patent grant or registration of a utility model or design, are reserved.

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte vorbehalten, insbesondere fuer den Fall der Patenterteilung oder GK-Entragung.






Confie a titre de secret d'entreprise. Tous droits reserves. Confiado como secreto Industrial. Nos reservados todos los derechos Comunicado como segredo empresarial. Reservados todos os direitos

DE - shaft extension
version with featherkey



deviation acc. to
DIN 6885 sheet 1

DIN 332 - DR M12



Type of construction: IM B5 (IM V1, IM V3) / Type of protection: IP55

			
Terminal box		gk803	1PH8083-1HF02-2GA2
Weight		32 kg	
Unit		mm [in]	
Date		4/25/23	
SIEMENS AG			DT
not toleranced dimensions: ± 1			