



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8107-1SG02-3LC1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	12.0	50.0	26.0	406	78.6	2,300	120	60.0	12,000	63.0	29	0.909	0.780	13.0
	BLM/SLM 400V	10.5	50.0	26.0	355	68.6	2,000	120	60.0	12,000	63.0	29	0.897	0.780	12.9
	ALM/BLM/SLM 480V	13.0	47.0	24.0	460	90.0	2,650	120	60.0	12,000	63.0	29	0.932	0.770	12.8

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	100
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	SPECIAL/B
Shaft and flange accuracy	SPECIAL
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Performance
Shaft end	Smooth hollow shaft
Encoder system	Incremental encoder 19 bit without commutation position (encoder IN19DQ)

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.13 A
3 AC 400 V / 60 Hz (±10%)	0.09 A
3 AC 480 V / 60 Hz (±10%)	0.13 A

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Physical constants

Thermal time constant	20 min
Moment of inertia	289 kgcm ²
Weight (approx.)	73 kg


Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	NDE
Signal connection	left
Terminal box designation	gk813


Cooling data and sound pressure level

Airflow, min.	0.04 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	110 Pa

Confie a titre de secret d'entreprise. Tous droits réservés.
Confido como secreto industrial. Nos reservamos todos los derechos
Comunicado como segredo empresarial. Reservados todos os direitos



/ Type of protection: IP55



not toleranced dimensions: ± 1

1PH8107-1SG02-3LC1

--	--

	DT
--	----