

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8131-1JS00-2BA2



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	14.6	70.0	39.0	302	68.2	2,000	200	111.0	8,000	94.0	47	0.908	0.840	15.9
	BLM/SLM 400V	11.0	70.0	39.0	227	51.5	1,500	200	111.0	8,000	94.0	47	0.884	0.850	15.1
	ALM/BLM/SLM 480V	18.0	69.0	38.0	372	84.8	2,500	200	111.0	8,000	94.0	47	0.922	0.840	15.6
Δ	ALM 400V	14.6	28.0	40.0	360	167.5	5,000	80	114.0	8,000	55.0	56	0.897	0.780	18.5
	BLM/SLM 400V	11.0	28.0	40.0	285	134.1	4,000	80	114.0	8,000	55.0	56	0.893	0.750	18.1
	ALM/BLM/SLM 480V	18.0	29.0	35.0	453	200.8	6,000	80	114.0	8,000	55.0	56	0.908	0.750	20.2

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder HTL 2048 S/R, max. encoder speed = 4600 rpm

Physical constants

Thermal time constant	30 min
Moment of inertia	590 kgcm ²
Weight (approx.)	89 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk846

Cooling data and sound pressure level

Airflow, min.	0.09 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	140 Pa

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.21 A
3 AC 400 V / 60 Hz (±10%)	0.19 A
3 AC 480 V / 60 Hz (±10%)	0.23 A

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

