



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8133-1DG00-0GH1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	22.5	93.0	44.0	400	78.1	2,300	250	117.0	8,000	126.0	54	0.933	0.840	18.1
	BLM/SLM 400V	20.0	96.0	45.0	350	68.1	2,000	250	117.0	8,000	126.0	54	0.919	0.850	18.1
	ALM/BLM/SLM 480V	24.0	86.0	41.0	456	89.6	2,650	250	117.0	8,000	126.0	54	0.949	0.830	18.1

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Plain shaft
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.21 A
3 AC 400 V / 60 Hz (±10%)	0.19 A
3 AC 480 V / 60 Hz (±10%)	0.23 A

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Physical constants

Thermal time constant	30 min
Moment of inertia	760 kgcm ²
Weight (approx.)	106 kg

Connection

Type of electrical connection	Power connector
Position of the connection	Power connector, top
Power connection	DE
Signal connection	left

Cooling data and sound pressure level






Airflow, min.	0.09 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	140 Pa

Confie a titre de secret d'entreprise. Tous droits reserves.
Confidado como secreto industrial. Nos reservados todos los derechos
Comunicado como segredo empresarial. Reservados todos os direitos

Weitergabe sowie Vervielfaeltigung dieser Unterlage. Verwer-
tung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht
ausdruecklich zugestanden. Zuwiderhandlungen verpflichten
zu Schadenersatz. Alle Rechte vorbehalten, insbesondere fuer
den Fall der Patenterteilung oder GK-Entragung.

The reproduction or use of this document or its
contents is not permitted without express written authority.
Diffenders will be liable for damages. All rights, including rights
created by patent grant or registration of a utility model or design,
are reserved.

Copyright© Siemens AG 2005
Cada-drawing do not make any
manual changes



Type of construction: IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8) of protection: IP55

		1PH8133-1DG00-0GH1	
Terminal box	-	-	
Weight	106 kg		
Unit	mm (in)		
Date	4/24/23	DT	
SIEMENS AG		not toleranced dimensions: ± 1	