

Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8137-1DG00-1BA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	29.0	120.0	56.0	400	77.9	2,300	340	152.0	8,000	176.0	73	0.929	0.860	21.9
	BLM/SLM 400V	28.0	134.0	60.0	350	68.1	2,000	340	152.0	8,000	176.0	73	0.924	0.870	21.5
	ALM/BLM/SLM 480V	30.0	108.0	52.0	460	89.4	2,650	340	152.0	8,000	176.0	73	0.941	0.830	22.4

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft end	Feather key with full key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.21 A
3 AC 400 V / 60 Hz (±10%)	0.19 A
3 AC 480 V / 60 Hz (±10%)	0.23 A

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Physical constants

Thermal time constant	30 min
Moment of inertia	1,090 kgcm ²
Weight (approx.)	141 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833


Cooling data and sound pressure level

Airflow, min.	0.09 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	140 Pa






Copyright© Siemens AG 2005
The reproduction or use of this document or its contents is not permitted without express written authority. Siemens AG and its subsidiaries are not liable for damages. All rights, including rights of patent, are reserved.
Weitergabe sowie Vervielfältigung dieser Unterlage, Vervielfältigung und Mitteilung ihres Inhalts ist ohne schriftliche Genehmigung Siemens AG und ihrer Tochtergesellschaften ist ausdrücklich untersagt. Alle Rechte, insbesondere die Patentrechte, sind vorbehalten. Inanspruchnahme der Patente durch Siemens AG oder ihre Tochtergesellschaften ist vorbehalten.
Confido como secreto industrial. No reservados todos los derechos. Reservados todos los derechos. Reservados todos los derechos.

DE - shaft extension
version with featherkey

deviation acc. to
DIN 6885 sheet 1



DIN 332 - DR M16



Type of construction: IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8) Protection: IP55

			
Terminal box		gk833	1PH8137-1DG00-1BA1
Weight		141 kg	
Unit		mm [in]	
Date		4/28/23	
SIEMENS AG		DT	
not toleranced dimensions: ± 1			