



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8137-3DF02-0AH1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	25.0	136.0	56.0	352	59.6	1,750	380	151.0	4,500	172.0	68	0.907	0.850	23.1
	BLM/SLM 400V	22.0	140.0	56.0	308	51.3	1,500	380	151.0	4,500	172.0	68	0.904	0.840	24.2
	ALM 480V	30.0	130.0	53.0	440	74.6	2,200	380	151.0	4,500	172.0	68	0.992	0.830	23.1
	BLM/SLM 480V	28.0	134.0	55.0	401	67.9	2,000	380	151.0	4,500	172.0	68	0.931	0.840	23.1

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Plain shaft
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	30 min
Moment of inertia	1,231 kgcm ²
Weight (approx.)	187 kg

Connection

Type of electrical connection	Power connector
Position of the connection	Power connector, top
Power connection	DE
Signal connection	left

Cooling data and sound pressure level

Airflow, min.	0.09 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	140 Pa

Holding brake

Holding torque	140 ... 310 Nm ²⁾
Moment of inertia	141 kgcm ²
Power supply voltage	V ± 10%
Coil current	A
Permissible brake work	15.5 kJ
Speed (Emergency Stop)	3,600 rpm
Number of emergency stops	2,000
Number of emergency stops per hour	3
Opening time	650 ms
Closing time	100 ms

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.10 A
3 AC 400 V / 60 Hz (±10%)	0.12 A
3 AC 480 V / 60 Hz (±10%)	0.12 A

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm
²⁾ Holding torque [Nm]: On motors with shaft height 100 ... 160, the holding torque can be gradually set using an adjusting ring within the value range specified (factory setting 100 % of the possible holding torque). The dynamic braking torque is approx. 70 % of the set holding torque.