



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8165-1DF10-2GA1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Engineering data

|   |                  | P <sub>N</sub><br>[kW] | M <sub>N</sub><br>[Nm] | I <sub>N</sub><br>[A] | U <sub>N</sub><br>[V] | f <sub>N</sub><br>[Hz] | n <sub>N</sub><br>[rpm] | M <sub>max</sub><br>[Nm] | I <sub>max</sub><br>[A] | n <sub>max</sub><br>[rpm] | M <sub>0</sub><br>[Nm] | I <sub>0</sub><br>[A] | η     | cos φ | I <sub>μ</sub><br>[A] |
|---|------------------|------------------------|------------------------|-----------------------|-----------------------|------------------------|-------------------------|--------------------------|-------------------------|---------------------------|------------------------|-----------------------|-------|-------|-----------------------|
| Y | ALM 400V         | 41.0                   | 224.0                  | 76.0                  | 400                   | 59.1                   | 1,750                   | 630                      | 206.0                   | 6,500                     | 304.0                  | 95                    | 0.934 | 0.880 | 25.8                  |
|   | BLM/SLM 400V     | 37.0                   | 236.0                  | 78.0                  | 350                   | 50.8                   | 1,500                   | 630                      | 206.0                   | 6,500                     | 304.0                  | 95                    | 0.926 | 0.880 | 27.0                  |
|   | ALM/BLM/SLM 480V | 45.0                   | 215.0                  | 75.0                  | 440                   | 67.5                   | 2,000                   | 630                      | 206.0                   | 6,500                     | 304.0                  | 95                    | 0.936 | 0.890 | 23.6                  |

Mechanical data

|                           |                                                                                             |
|---------------------------|---------------------------------------------------------------------------------------------|
| Motor type                | Squirrel cage asynchronous motor                                                            |
| Shaft height              | 160                                                                                         |
| Cooling                   | Forced ventilation NDE -> DE                                                                |
| Vibration severity grade  | R/A                                                                                         |
| Shaft and flange accuracy | R                                                                                           |
| Degree of protection      | IP55                                                                                        |
| Design acc. to Code I     | IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)                                                   |
| Temperature monitoring    | Pt1000 temperature sensor in the stator winding                                             |
| Color                     | Standard (Anthracite RAL 7016)                                                              |
| Type of the bearing       | Standard                                                                                    |
| Shaft end                 | Feather key with half key balancing                                                         |
| Encoder system            | Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm |

External fan

Max. power consumption

|                           |        |
|---------------------------|--------|
| 3 AC 400 V / 50 Hz (±10%) | 0.17 A |
| 3 AC 400 V / 60 Hz (±10%) | 0.22 A |
| 3 AC 480 V / 60 Hz (±10%) | 0.22 A |

<sup>1)</sup> at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Physical constants

|                       |                         |
|-----------------------|-------------------------|
| Thermal time constant | 35 min                  |
| Moment of inertia     | 2,320 kgcm <sup>2</sup> |
| Weight (approx.)      | 230 kg                  |

Connection

|                               |              |
|-------------------------------|--------------|
| Type of electrical connection | Terminal box |
| Position of the connection    | NDE top      |
| Power connection              | right        |
| Signal connection             | DE           |
| Terminal box designation      | gk863        |

Cooling data and sound pressure level

|                                                                                               |                     |
|-----------------------------------------------------------------------------------------------|---------------------|
| Airflow, min.                                                                                 | 0.16 m³/s           |
| Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB | 73 dB <sup>1)</sup> |
| Air discharge                                                                                 | axial               |
| Pressure drop                                                                                 | 200 Pa              |


Confie a titre de secret d'entreprise. Tous droits réservés.  
Confiado como secreto industrial. Nos reservamos todos los derechos  
Comunicado como segredo empresarial. Reservados todos os direitos

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte vorbehalten, insbesondere fuer den Fall der Patenterteilung oder der Eintragung.






The reproduction or use of this document or its contents is not permitted without express written authority. Offenders will be liable for damages. All rights, including rights created by patent grant or registration of a utility model or design, are reserved.

Copyright© Siemens AG 2005  
Cada-drawing do not make any manual changes

DE - shaft extension  
version with featherkey



DIN 332 - DR M20



Type of construction: IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8) Protection: IP55

|                                                                                       |         |                    |
|---------------------------------------------------------------------------------------|---------|--------------------|
|  |         |                    |
|                                                                                       |         |                    |
| Terminal box                                                                          | gk863   | 1PH8165-1DF10-2GA1 |
| Weight                                                                                | 230 kg  |                    |
| Unit                                                                                  | mm (in) |                    |
| Date                                                                                  | 5/3/23  |                    |
| SIEMENS AG                                                                            |         | DT                 |
| not toleranced dimensions: ± 1                                                        |         |                    |