



Catalog #: 20BR180A3NNNACD1

PowerFlex 700 AC Drive 20B

Lifecycle status: **Fim do ciclo de vida**

Rockwell Automation announces that as of June 1, 2023, the PowerFlex 700 AC Drive 20B will be discontinued and no longer available for sale. Customers are encouraged to remove references to the affected product(s).

Discontinued Date:

June 1, 2023

Replacement Category:

Direct Replacement

Produto de reposição:

[20BR180A0NNNACD1](https://www.rockwellautomation.com/pt-br/products/details.20BR180A0NNNACD1) and [20-HIM-A6](https://www.rockwellautomation.com/pt-br/products/details.20-HIM-A6)

[<https://www.rockwellautomation.com/pt-br/products/details.20BR180A0NNNACD1> and [20-HIM-A6.html](https://www.rockwellautomation.com/pt-br/products/details.20-HIM-A6)]

Technical Specifications

Mechanical

Degree of protection (IP)	IP20
Shock	15 G peak for 11 ms duration (±1.0 ms)
PWM frequency	4 kHz @ 650V DC
Vibration	0.152 mm (0.006 inch) displacement, 1 G peak

Electrical

Number of analogue outputs	2
Mains voltage	650 V
Integrated breaking resistance	No
Brake IGBT	Without brake IGBT
Internal communication module	ControlNet coaxial
Fuse current rating	400 A @ 650V DC
Input voltage rating	650V DC precharge
Output current rating, continuous	180 A @ 650V DC, normal duty
Output current rating, 1 min	234 A @ 650V DC, heavy duty
Output current rating, 3 sec	312 A @ 650V DC, heavy duty
Logic control ride-thru	0.5 seconds minimum, 2 seconds typical

Brake resistor	No internal brake resistor
Input current rating	204 A @ 650V DC, 150 Hp normal duty
Documentation	No manual
Carrier frequency	2, 4, 8, and 10 kHz. Drive rating based on 4 kHz
Encoder quadrature	90 degrees, ± 27 degrees at 25 °C (77 °F)
Digital input latency, typical	9.2 ms @ stop signal for SVC motor control
Heat sink thermistor	Monitored by microprocessor overtemp trip
Digital input latency	9.2...16.0 ms @ start signal for SVC motor control
Drive to motor power ratio, max	Recommended not greater than 2:1 ratio
Stop modes	Multiple programmable stop modes including – Ramp, Coast, DC-brake, Fast brake, Ramp-to-hold and S-curve
Frequency accuracy	Digital input: within $\pm 0.01\%$ of set output frequency
Acceleration/deceleration	Two independently programmable accel and decel times. Each time can be programmed from 0...3600 seconds in 0.1 second increments
Analog input latency, typical	6.4 ms @ speed signal for SVC motor control
Number of digital inputs	6
Number of digital outputs	3
Number of analogue inputs	2
Supporting protocol for DeviceNet	Yes
Human interface model	LCD display full numeric keypad with programming keys
Max. output frequency	420 Hz
Supporting protocol for EtherNet/IP	Yes
Actual short circuit rating	Determined by AIC rating of installed fuse/circuit breaker
Internal EMC filtering	With EMC filter with common mode choke
Custom drive/firmware	No custom firmware
Feedback option	Standard encoder
Analog input latency	4.8...12.4 ms @ speed signal for SVC motor control
Torque regulation	With feedback: $\pm 2\%$, 2500 rad/sec bandwidth
Enclosure type	IP20/NEMA/UL Type 1
Output current rating	180 amps, 150 Hp normal duty, 125 Hp heavy duty, frame 6
Control options	Vector control with 115V AC I/O
Drive overcurrent trip	Instantaneous current limit: 220...300% of rated current (dependent on drive rating)

Efficiency	97.5% at rated amps, nominal line volts
Encoder supply	12V, 250 mA. 12V, 10 mA minimum inputs isolated with differential transmitter, 250 kHz maximum
Speed control-speed regulation	Without feedback (Vector Control Mode): 0.1 % of base speed across 120:1 speed range, 120:1 operating range, 50 rad/sec bandwidth
Current limit capability	Proactive current limit programmable from 20...160% of rated output current, Independently programmable proportional and integral gain
Selectable motor control	Sensorless vector with full tuning. Standards V/Hz with full custom capability and vector control
Frequency control-speed regulation	With slip compensation (Volts per Hertz mode): 0.5% of base speed across 40:1 speed range, 40:1 operating range, 10 rad/sec bandwidth
Input phases	3-phase input provides full rating for all drives. 1-phase operation possible on certain drives and provides 50 % of rated current. Frames 0...6: drive can be supplied as 6 pulse or 18 pulse in an engineered package.
Control method	Sine coded PWM with programmable carrier frequency, ratings apply to all drives, the drive can be supplied as 6 pulse or 18 pulse in an engineered solution
Encoder requirements	Encoders must be line driver type, quadrature (dual channel) or pulse (single channel), 8...15V DC output (4...6V DC when jumpers are in 5V position), single-ended or differential and capable of supplying a min. of 10 mA per channel, maximum input frequen
Number of phases output	3
Number of phases input	3
Relative symmetric net voltage tolerance	10 %
With control element	Yes
Supporting protocol for LON	Yes
Supporting protocol for TCP/IP	Yes
Supporting protocol for PROFIBUS	Yes
Supporting protocol for CAN	Yes
Supporting protocol for Modbus	Yes
Motor overload protection	Frames 0...6 vector control: powerflex 700 drives with vector control, which is identified by a C or D in position 15 of the catalog number, provide class 10 motor overload protection according to NEC article 430 and motor overtemperature protection acco
Input frequency tolerance	47 Hz
Encoder duty cycle	50% ±10%
Displacement power factor (all drives)	0.98 across speed range
Short circuit rating, max	200000 amps symmetrical

Output voltage range	0 to rated motor voltage
Encoder type	Incremental, dual channel
Power ride-thru	15 milliseconds at full load
Short circuit trip	Phase-to-phase on drive output
Ground fault trip	Phase-to-ground on drive output
Drive to motor power ratio, min	Recommended not less than 1:2 ratio
Control logic noise immunity	Showering arc transients upto 1500V peak
Line transients	Up to 6000 volts peak per IEEE C62.41-1991
Intermittent overload	110% overload capability for up to 1 minute, 150% overload capability for up to 3 seconds

Construction

Height, approx	IP54, NEMA type 12 standalone: 1828.8 mm
Depth, approx	IP54, NEMA type 12 standalone: 487.8 mm
Width, approx	IP54, NEMA type 12 standalone: 711.3 mm
Weight, approx	IP54, NEMA type 12 standalone: 229.07 kg (drive and packaging weight)

Environmental

Sound level	Frame 6: 72 dB @ 300 CFM fan velocity
Altitude	1000 m (3300 ft.) maximum without derating
Degree of protection (NEMA)	1
Surrounding air temperature	IP20, NEMA/UL type 1 (with top label): 0...50 °C (0...122 °F) @ frames 5...6, most ratings
Atmosphere	Drive must not be installed in an area where the ambient atmosphere contains volatile or corrosive gas, vapors or dust, If the drive is not going to be installed immediately, store the drive where it is not exposed to a corrosive atmosphere
Operating temperature	50 °C @ 650V DC
Storage temperature	-40 °C
Relative humidity	5...95% noncondensing
Pollution degree 1 according to EN 61800-5-1	No pollution occurs, only dry non-conductive pollution occurs, and has no influence
Pollution degree 4 according to EN 61800-5-1	The pollution generates persistent conductivity caused, for example, by conductive dust, rain or snow
Pollution degree 3 according to EN 61800-5-1	Conductive pollution occurs, dry non-conductive pollution occurs and becomes conductive due to condensation
Pollution degree 2 according to EN 61800-5-1	Normally only non-conductive pollution occurs, Occasionally a temporary conductivity, caused by

condensation is expected when the drive is out of operation

Surrounding environment pollution degree

All enclosures are acceptable for pollution degree 1 and 2, an enclosure that meets or exceeds IP54, NEMA/UL Type 12, is required for pollution degree 3 and 4



Copyright ©2022 Rockwell Automation, Inc.