



undervoltage release 120-127 V AC 50/60 Hz accessory for: 3VA1 and 3VA20-26

| Model                                                                                                                                                          |                   |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| product brand name                                                                                                                                             | SETRON            |
| product designation                                                                                                                                            | Auxiliary release |
| accessories                                                                                                                                                    | Auxiliary release |
| General technical data                                                                                                                                         |                   |
| degree of pollution                                                                                                                                            | 3                 |
| overvoltage category                                                                                                                                           | III               |
| apparent power consumption / maximum                                                                                                                           | 2 VA              |
| Voltage                                                                                                                                                        |                   |
| surge voltage resistance                                                                                                                                       | 4 kV              |
| Mechanical Design                                                                                                                                              |                   |
| height                                                                                                                                                         | 65.1 mm           |
| width                                                                                                                                                          | 25.7 mm           |
| number of slots                                                                                                                                                | 3                 |
| depth                                                                                                                                                          | 28.8 mm           |
| net weight                                                                                                                                                     | 91 g              |
| tightening torque / with screw-type terminals / minimum                                                                                                        | 0.4 N·m           |
| tightening torque / with screw-type terminals / maximum                                                                                                        | 0.5 N·m           |
| Connections according IEC                                                                                                                                      |                   |
| stripped length                                                                                                                                                | 10 mm             |
| connectable conductor cross-section <ul style="list-style-type: none"><li>• minimum</li><li>• maximum</li></ul>                                                | 0.5 ... 1.5       |
| AWG number / as coded connectable conductor cross section / for auxiliary contacts <ul style="list-style-type: none"><li>• minimum</li><li>• maximum</li></ul> |                   |
|                                                                                                                                                                | 20                |
|                                                                                                                                                                | 16                |
| Connetctions according UL                                                                                                                                      |                   |
| stripped length [in]                                                                                                                                           | 0.4 in            |
| tightening torque [lbf·in] / with screw-type terminals / minimum                                                                                               | 3.5 lbf·in        |
| tightening torque [lbf·in] / with screw-type terminals / maximum                                                                                               | 4.4 lbf·in        |
| Certificates                                                                                                                                                   |                   |
| General Product Approval                                                                                                                                       |                   |
| EMV                                                                                                                                                            |                   |
| Test Certificates                                                                                                                                              |                   |



[Miscellaneous](#)



[Type Test Certificates/Test Report](#)

| Test Certificates             | Marine / Shipping                                                                 | other                        |                               |                               | Environment                                       |
|-------------------------------|-----------------------------------------------------------------------------------|------------------------------|-------------------------------|-------------------------------|---------------------------------------------------|
| <a href="#">Miscellaneous</a> |  | <a href="#">Confirmation</a> | <a href="#">Miscellaneous</a> | <a href="#">Miscellaneous</a> | <a href="#">Environmental Con-<br/>firmations</a> |

## Environment

[Environmental Con-  
firmations](#)

## Further information

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9908-0BB24>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9908-0BB24>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA9908-0BB24](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9908-0BB24)


### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>





last modified:

5/26/2024 

