



LV HRC fuse element, NH00, In: 100 A, gG, Un AC: 400 V, Combined indicator, insulated Grip lugs

Model	
product brand name	SETRON
product designation	LV HRC fuse link
design of the product	With blade contacts
design of an identification indicator	Combination alarms
design of the switching contact	Non-corroding, silver-plated
design of the fuse link	LV HRC fuse link
General technical data	
size of fuse system according to EN 60269-1	NH00
mounting type	insulated grip lugs
type of voltage of the operating voltage	AC
supply voltage	
• at AC	400 V
Protection class	
protection class IP	IP20, with connected conductors
Breaking Capacity	
breaking capacity	
• at AC according to IEC 60269 rated value	120 kA
Dissipation	
power loss [W]	5.82 W
power loss [W] for rated value of the current at AC in hot operating state per pole	5.82 W
Mechanical Design	
width of the enclosure	30 mm
mounting position	Any, preferably vertical
net weight	204 g
Environmental conditions	
ambient temperature during operation	
• minimum	-5 °C
• maximum	40 °C
environmental category	-20 to +50 at 95% relative humidity
environmental category during storage	90% at 20°C
Environmental footprint	
global warming potential [CO2 eq] total	10.4 kg
global warming potential [CO2 eq] during manufacturing	2.38 kg
global warming potential [CO2 eq] during operation	8 kg
global warming potential [CO2 eq] after end of life	-0.082 kg
Certificates	
reference code according to IEC 81346-2	FC
Approvals Certificates	


[Confirmation](#)


other

Environment

[Miscellaneous](#)
[Confirmation](#)
[Miscellaneous](#)

[Environmental Con-
firmations](#)
[Environmental Con-
firmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NA6830-4KK>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NA6830-4KK>


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA6830-4KK

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>


-F



FU



