

## Data sheet

6ES7590-0BH00-0AA0

SIMATIC S7-1500 / ET 200MP active backplane bus 8 slots for inserting S7-1500 I/O modules for hot swapping for use in the ET 200MP with IM 155-5 PN HF (from FW V4.4.1); S7-1500 mounting rail and slot covers to be ordered separately



Figure similar

General information	
Product type designation	Active Backplane ST 1+8 Slot
HW functional status	from FS01
Firmware version	from V1.0.0
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	Yes
• Prioritized startup	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V16 / V17
• STEP 7 configurable/integrated from version	V5.6 and higher
• PROFINET from GSD version/GSD revision	V2.35 / -
Power	
Power available from the backplane bus	2 W
Power loss	
Power loss, typ.	2 W
Hardware configuration	
Slots	
• Grid size	35 mm; Utilization of 25 mm-wide modules possible
• Number of slots	9
— of which for CPU, max.	1; for S7-1500H CPU with CPU firmware V3.1 or higher; interface modules up to V1.1.0 only (active backplane bus)
— of which for IM, max.	1
— of which for PS, max.	8; Max. 2 PS per station
— of which for IO/CM/CP/TM, max.	8
— of which for F-IO, max.	8
• Number of single-width slots, max.	8
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C
• vertical installation, max.	40 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual

<b>Dimensions</b>	
Width	294 mm
Height	99 mm
Depth	14 mm
<b>Weights</b>	
Weight, approx.	246 g

**last modified:** 11/8/2024 