



Technical Specifications

Tables 3...6 summarize the technical specifications for PanelView Standard terminals.

PanelView Standard 300 Micro and 300 Terminals

Table 3 - Technical Specifications - PanelView Standard 300 Micro/300 Terminals



Attribute	PanelView 300 Micro 2711-M3A18L1, 2711-M3A19L1	PanelView 300 2711-K3A2L1, 2711-K3A5L1, 2711-K3A5L1K, 2711-K3A10L1, 2711-K3A17L1
Operator input	Keypad	Keypad
Display type	Monochrome transfective LCD with LED backlight	
Display area (WxH)	73 x 42 mm (2.87 x 1.67 in.)	
Resolution	128 x 64	
Backlight	100,000 hr LED backlight life	
Touch screen	—	—
Keypad description	Stainless steel domed membrane Navigation, function keys Actuation: 2 million presses	
Keypad function keys	4 function keys (F1...F4)	8 function keys (F1...F8)
Real-time clock	Battery-backed clock timestamps critical data	
Battery	Not replaceable	
Application memory	170 KB application runtime 240 KB nonvolatile memory (application objects plus text and bitmaps)	
ATA memory card	Not supported	Supported
Software	PanelBuilder32 software, runs on a personal computer	
Communication ports	RS-232 (DH-485) RS-232 (DF1)	DeviceNet DH-485 RS-232 (DH-485) RS-232 (DF1)
RS-232 printer port	—	1200, 2400, 9600, 19,200 Kbps
Input voltage, DC	11...30V DC (24V DC nom)	18...32V DC (24V DC nom)
Power consumption, DC	25 W max (0.105 A at 24V DC)	10 W max (0.42 A at 24V DC)
Input voltage, AC	—	—
Power consumption, AC	—	—
Weight, approx.	284 g (10 oz.)	673 g (1.48 lb)
Dimensions (HxWxD), approx.	133 x 111 x 48 mm 5.23 x 4.38 x 1.87 in.	197 x 140 x 82 mm 7.76 x 5.53 x 3.21 in.