



SIPLUS CMS VIB-Sensor S02 Vibration sensor; Frequency range 1Hz to 15kHz; Measuring range 500G; Sensitivity 10mV/G (+/-10%); MIL connector on top

General information	
Product type designation	VIB-Sensor S02
Product description	piezoelectric sensor for connection to SIPLUS CMS1200 or SIPLUS CMS2000
Installation type/mounting	
Installation and mounting instructions	incl. mounting bolts UNF1/4-28 on M6 and M8
Input current	
Type of power supply	IEPE 2 to 10 mA
Encoder	
Encoder signals, IEPE	
<ul style="list-style-type: none"> • Signal voltage (DC), min. • Signal voltage (DC), max. 	10 V 14 V
Integrated Functions	
Measuring functions	
<ul style="list-style-type: none"> • Physical measuring principle • Operating range of sensor at +/- 3 dB, min. • Operating range of sensor at +/- 3 dB, max. • Resonance frequency 	Piezo-quartz recorder with integrated evaluation electronics 1 Hz 15 000 Hz 23 kHz
Measuring range	
<ul style="list-style-type: none"> — Measurement range vibration acceleration, max. — Sensitivity, typ. 	500 gn 10 mV/gn
Degree and class of protection	
IP degree of protection	IP65
Standards, approvals, certificates	
CE mark	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
China RoHS compliance	Yes
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. • max. 	-50 °C 121 °C
Cables	
Cable length, max.	30 m
Connection method	
Type of connection	MIL-C5015
Mechanics/material	
Material of housing	Stainless steel

Classifications

	Version	Classification
eClass	14	27-20-14-12
eClass	12	27-20-14-12
eClass	9.1	27-20-14-12
eClass	9	27-20-14-12
eClass	8	27-20-14-04
eClass	7.1	27-20-14-04
eClass	6	27-20-14-04
ETIM	10	EC002961
ETIM	9	EC002961
ETIM	8	EC002961
ETIM	7	EC002961

Approvals / Certificates

General Product Approval	EMV
--------------------------	-----



[China RoHS](#)



last modified:

5/9/2025