




Accessory 3WA/3WL Undervoltage release (UVR-t), with time delay 0,2-3,2 s 48 V DC,

Model	
product brand name	SETRON
product designation	Undervoltage release
design of the product	undervoltage release (UVR-t), time delay 0.2 to 3.2 s, 60 V DC
design of the fuse link	fuse gG: 2 A, miniature circuit breaker C characteristic: 4 A, miniature circuit breaker D characteristic: 2 A
closing active power [W]	50 W
operating active power [W]	5 W
OFF-delay time minimum	200 ms
OFF-delay time maximum	3 200 ms
ambient temperature during operation	
• minimum	-40 °C
• maximum	70 °C
ambient temperature during storage	
• minimum	-40 °C
• maximum	80 °C

Approvals Certificates	
General Product Approval	Test Certificates



[Confirmation](#)



[Type Test Certificates/Test Report](#)

Test Certificates	Marine / Shipping	other	Dangerous goods
-------------------	-------------------	-------	-----------------

[Special Test Certificate](#)





LRS

[Confirmation](#)

[Dangerous goods information](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WA9111-0AE13>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3WA9111-0AE13>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WA9111-0AE13



last modified:

9/9/2024 

