

PRODUCT-DETAILS

ACS580-01-073A-4

ACS580-01-073A-4 PN: 37 kW, IN: 73 A



General Information

Global Commercial Alias	ACS580-01-073A-4
Product ID	3AUA0000080499
ABB Type Designation	ACS580-01-073A-4
EAN	6438177305552
Catalog Description	ACS580-01-073A-4 PN: 37 kW, IN: 73 A

Long Description	The ACS580-01 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture.
	All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The wall-mounted ACS580-01 comes in IP21 enclosure as standard. Also, IP55 and flange mounting units are available.

Ordering

Country of Origin	Finland (FI)
Customs Tariff Number	85044084
Invoice Description	ACS580-01-073A-4 PN: 37 kW, IN: 73 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece

Quote Only	No
Selling Unit of Measure	piece

Container Information

Gross Volume	33.181 dm³
--------------	------------

Dimensions

Product Net Weight	20 kg
Product Net Depth / Length	257 mm
Product Net Height	636 mm
Product Net Width	203 mm
Package Level 1 Depth / Length	760 mm
Package Level 1 Height	428 mm
Package Level 1 Width	298 mm
Package Level 1 Units	1 carton

Technical

Number of Phases	3
Degree of Protection	acc. to IEC 60529 IP21
Enclosure Type NEMA	Type1
Altitude	1000 m
	95
Sound dB (A)	69 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47 ... 63 Hz
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	With control unit Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 3
Output Current, Heavy-	61 A
Duty Use (I _{HD})	
Output Current, Light-	68 A

Overload Use (I_{LD})

Output Current, Normal	73 A
------------------------	------

Use (I_n)

Output Power, Heavy-	30.0 kW
----------------------	---------

Duty Use (P_{HD})

Output Power, Light-	37 kW
----------------------	-------

Overload Use (P_{LD})

Output Power, Normal	37 kW
----------------------	-------

Use (P_n)

Apparent Power Output	51 kV-A
-----------------------	---------

Efficiency Level	IE2
------------------	-----

Standby Loss	19 W
--------------	------

Complete Drive Module

Efficiency (61800-9-2)

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	295 W	90.1 %	0.6 %
0/50 %	392 W	93.0 %	0.8 %
0/100 %	726 W	93.4 %	1.4 %
50/25 %	324 W	94.5 %	0.6 %
50/50 %	454 W	96.0 %	0.9 %
50/100 %	866 W	96.1 %	1.7 %
90/50 %	527 W	97.4 %	1.0 %
90/100 %	1120 W	97.2 %	2.2 %

Temperature Rating

Maximum 40 °C
Minimum -15 °C

Additional Information

Product Main Type	ACS580-01
-------------------	-----------

Product Name	Frequency converter
--------------	---------------------

Classifications

ETIM 7	EC001857 - Frequency converter =< 1 kV
--------	--

UNSPSC	39122001
--------	----------

Environmental

SCIP	596c7575-1ed1-48e9-be9a-d8fdd900606b Finland (FI)
------	---

WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
---------------	---

Categories

Drives → Low Voltage AC Drives → General Purpose Drives → ACS580-01 - Wall-mounted drive

