

Siemens  
EcoTech



SIRIUS soft starter 200-690 V 470 A, 110-250 V AC Screw terminals



|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| product brand name            | SIRIUS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| product category              | Hybrid switching devices                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| product designation           | Soft starter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| product type designation      | 3RW55                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| manufacturer's article number | <ul style="list-style-type: none"> <li>• of high feature HMI module usable <a href="#">3RW5980-0HF00</a></li> <li>• of communication module PROFINET standard usable <a href="#">3RW5980-0CS00</a></li> <li>• of communication module PROFINET high-feature usable <a href="#">3RW5950-0CH00</a></li> <li>• of communication module PROFIBUS usable <a href="#">3RW5980-0CP00</a></li> <li>• of communication module Modbus TCP usable <a href="#">3RW5980-0CT00</a></li> <li>• of communication module Modbus RTU usable <a href="#">3RW5980-0CR00</a></li> <li>• of communication module Ethernet/IP <a href="#">3RW5980-0CE00</a></li> <li>• of circuit breaker usable at 400 V <a href="#">3VA2450-7MN32-0AA0; Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of circuit breaker usable at 500 V <a href="#">3VA2450-7MN32-0AA0; Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of circuit breaker usable at 400 V at inside-delta circuit <a href="#">3VA2510-6HN32-0AA0; Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of circuit breaker usable at 500 V at inside-delta circuit <a href="#">3VA2510-6HN32-0AA0; Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of the gG fuse usable up to 690 V 2x3NA3365-6; Type of coordination 1, Iq = 65 kA</li> <li>• of the gG fuse usable at inside-delta circuit up to 500 V 2x3NA3365-6; Type of coordination 1, Iq = 65 kA</li> <li>• of full range R fuse link for semiconductor protection usable up to 690 V <a href="#">3NE1436-2; Type of coordination 2, Iq = 65 kA</a></li> <li>• of back-up R fuse link for semiconductor protection usable up to 690 V <a href="#">3NE3340-8; Type of coordination 2, Iq = 65 kA</a></li> </ul> |

### General technical data

|                                       |                           |
|---------------------------------------|---------------------------|
| starting voltage [%]                  | 20 ... 100 %              |
| stopping voltage [%]                  | 50 %; non-adjustable      |
| start-up ramp time of soft starter    | 0 ... 360 s               |
| ramp-down time of soft starter        | 0 ... 360 s               |
| start torque [%]                      | 10 ... 100 %              |
| stopping torque [%]                   | 10 ... 100 %              |
| torque limitation [%]                 | 20 ... 200 %              |
| current limiting value [%] adjustable | 125 ... 800 %             |
| breakaway voltage [%] adjustable      | 40 ... 100 %              |
| breakaway time adjustable             | 0 ... 2 s                 |
| number of parameter sets              | 3                         |
| accuracy class                        | 5 (based on IEC 61557-12) |
| certificate of suitability            |                           |
| • CE marking                          | Yes                       |
| • UL approval                         | Yes                       |

|                                                              |                                                                                                                                                                                                                                                                                                                                                             |
|--------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • CSA approval                                               | Yes                                                                                                                                                                                                                                                                                                                                                         |
| <b>product component</b>                                     |                                                                                                                                                                                                                                                                                                                                                             |
| • HMI-High Feature                                           | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • is supported HMI-High Feature                              | Yes                                                                                                                                                                                                                                                                                                                                                         |
| <b>product feature integrated bypass contact system</b>      | Yes                                                                                                                                                                                                                                                                                                                                                         |
| <b>number of controlled phases</b>                           | 3                                                                                                                                                                                                                                                                                                                                                           |
| <b>current unbalance limiting value [%]</b>                  | 10 ... 60 %                                                                                                                                                                                                                                                                                                                                                 |
| <b>ground-fault monitoring limiting value [%]</b>            | 10 ... 95 %                                                                                                                                                                                                                                                                                                                                                 |
| <b>buffering time in the event of power failure</b>          |                                                                                                                                                                                                                                                                                                                                                             |
| • for main current circuit                                   | 100 ms                                                                                                                                                                                                                                                                                                                                                      |
| • for control circuit                                        | 100 ms                                                                                                                                                                                                                                                                                                                                                      |
| <b>idle time adjustable</b>                                  | 0 ... 255 s                                                                                                                                                                                                                                                                                                                                                 |
| <b>insulation voltage rated value</b>                        | 690 V                                                                                                                                                                                                                                                                                                                                                       |
| <b>degree of pollution</b>                                   | 3, acc. to IEC 60947-4-2                                                                                                                                                                                                                                                                                                                                    |
| <b>impulse voltage rated value</b>                           | 8 kV                                                                                                                                                                                                                                                                                                                                                        |
| <b>blocking voltage of the thyristor maximum</b>             | 1 800 V                                                                                                                                                                                                                                                                                                                                                     |
| <b>service factor</b>                                        | 1.15                                                                                                                                                                                                                                                                                                                                                        |
| <b>surge voltage resistance rated value</b>                  | 8 kV                                                                                                                                                                                                                                                                                                                                                        |
| <b>maximum permissible voltage for protective separation</b> |                                                                                                                                                                                                                                                                                                                                                             |
| • between main and auxiliary circuit                         | 690 V; does not apply for thermistor connection                                                                                                                                                                                                                                                                                                             |
| <b>shock resistance</b>                                      | 15 g / 11 ms, from 6 g / 11 ms with potential contact lifting                                                                                                                                                                                                                                                                                               |
| <b>vibration resistance</b>                                  | 15 mm up to 6 Hz; 2 g up to 500 Hz                                                                                                                                                                                                                                                                                                                          |
| <b>recovery time after overload trip adjustable</b>          | 60 ... 1 800 s                                                                                                                                                                                                                                                                                                                                              |
| utilization category according to IEC 60947-4-2              | AC 53a                                                                                                                                                                                                                                                                                                                                                      |
| <b>reference code according to IEC 81346-2</b>               | Q                                                                                                                                                                                                                                                                                                                                                           |
| <b>Substance Prohibitance (Date)</b>                         | 02/15/2018                                                                                                                                                                                                                                                                                                                                                  |
| <b>SVHC substance name</b>                                   | Lead - 7439-92-1<br>Lead monoxide (lead oxide) - 1317-36-8<br>2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol - 79-94-7<br>2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one - 71868-10-5<br>6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol - 119-47-1<br>Dibutylbis(pentane-2,4-dionato-O,O')tin - 22673-19-4<br>Lead titanium trioxide - 12060-00-3 |
| <b>Weight</b>                                                | 13.7 kg                                                                                                                                                                                                                                                                                                                                                     |
| <b>product function</b>                                      |                                                                                                                                                                                                                                                                                                                                                             |
| • ramp-up (soft starting)                                    | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • ramp-down (soft stop)                                      | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • breakaway pulse                                            | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • adjustable current limitation                              | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • creep speed in both directions of rotation                 | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • pump ramp down                                             | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • DC braking                                                 | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • motor heating                                              | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • min/max pointer                                            | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • trace function                                             | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • intrinsic device protection                                | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • motor overload protection                                  | Yes; Full motor protection (thermistor motor protection and electronic motor overload protection)                                                                                                                                                                                                                                                           |
| • evaluation of thermistor motor protection                  | Yes; Type A PTC or Klaxon / Thermoclick                                                                                                                                                                                                                                                                                                                     |
| • inside-delta circuit                                       | Yes; Only up to 600 V operating voltage                                                                                                                                                                                                                                                                                                                     |
| • auto-RESET                                                 | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • manual RESET                                               | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • remote reset                                               | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • communication function                                     | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • operating measured value display                           | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • event list                                                 | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • error logbook                                              | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • via software parameterizable                               | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • via software configurable                                  | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • screw terminal                                             | Yes                                                                                                                                                                                                                                                                                                                                                         |
| • spring-loaded terminal                                     | No                                                                                                                                                                                                                                                                                                                                                          |
| • PROFINergy                                                 | Yes; in connection with the PROFINET Standard and PROFINET High-Feature communication modules                                                                                                                                                                                                                                                               |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• <b>firmware update</b></li> <li>• <b>removable terminal for control circuit</b></li> <li>• voltage ramp</li> <li>• torque control</li> <li>• combined braking</li> <li>• analog output</li> <li>• programmable control inputs/outputs</li> <li>• condition monitoring</li> <li>• automatic parameterisation</li> <li>• application wizards</li> <li>• alternative run-down</li> <li>• emergency operation mode</li> <li>• reversing operation</li> <li>• soft starting at heavy starting conditions</li> </ul> | Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes; 4 ... 20 mA (default) / 0 ... 10 V<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes |
| <b>Power Electronics</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                    |
| <b>operational current</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 40 °C rated value</li> <li>• at 40 °C rated value minimum</li> <li>• at 50 °C rated value</li> <li>• at 60 °C rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                        | 470 A<br>94 A<br>416 A<br>380 A                                                                                                    |
| <b>operational current at inside-delta circuit</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 40 °C rated value</li> <li>• at 50 °C rated value</li> <li>• at 60 °C rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                | 814 A<br>721 A<br>658 A                                                                                                            |
| <b>operating voltage</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• rated value</li> <li>• at inside-delta circuit rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                          | 200 ... 690 V<br>200 ... 600 V                                                                                                     |
| <b>relative negative tolerance of the operating voltage</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | -15 %                                                                                                                              |
| <b>relative positive tolerance of the operating voltage</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 10 %                                                                                                                               |
| <b>relative negative tolerance of the operating voltage at inside-delta circuit</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | -15 %                                                                                                                              |
| <b>relative positive tolerance of the operating voltage at inside-delta circuit</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 10 %                                                                                                                               |
| <b>operating power for 3-phase motors</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 230 V at 40 °C rated value</li> <li>• at 230 V at inside-delta circuit at 40 °C rated value</li> <li>• at 400 V at 40 °C rated value</li> <li>• at 400 V at inside-delta circuit at 40 °C rated value</li> <li>• at 500 V at 40 °C rated value</li> <li>• at 500 V at inside-delta circuit at 40 °C rated value</li> <li>• at 690 V at 40 °C rated value</li> </ul>                                                                                                                                         | 132 kW<br>250 kW<br>250 kW<br>400 kW<br>315 kW<br>500 kW<br>400 kW                                                                 |
| <b>Operating frequency 1 rated value</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 50 Hz                                                                                                                              |
| <b>Operating frequency 2 rated value</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 60 Hz                                                                                                                              |
| <b>relative negative tolerance of the operating frequency</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | -10 %                                                                                                                              |
| <b>relative positive tolerance of the operating frequency</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 10 %                                                                                                                               |
| <b>minimum load [%]</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 10 %; Relative to set le                                                                                                           |
| <b>power loss [W] for rated value of the current at AC</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 40 °C after startup</li> <li>• at 50 °C after startup</li> <li>• at 60 °C after startup</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                          | 141 W<br>125 W<br>114 W                                                                                                            |
| <b>power loss [W] at AC at current limitation 350 %</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 40 °C during startup</li> <li>• at 50 °C during startup</li> <li>• at 60 °C during startup</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                       | 7 651 W<br>6 400 W<br>5 620 W                                                                                                      |
| <b>type of the motor protection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Electronic, tripping in the event of thermal overload of the motor                                                                 |
| <b>Control circuit/ Control</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                    |
| <b>type of voltage of the control supply voltage</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | AC                                                                                                                                 |
| <b>control supply voltage at AC</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 110 ... 250 V<br>110 ... 250 V                                                                                                     |
| <b>relative negative tolerance of the control supply voltage at</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | -15 %                                                                                                                              |

|                                                                          |                                                                                                                                                                                |
|--------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AC at 50 Hz</b>                                                       |                                                                                                                                                                                |
| relative positive tolerance of the control supply voltage at AC at 50 Hz | 10 %                                                                                                                                                                           |
| relative negative tolerance of the control supply voltage at AC at 60 Hz | -15 %                                                                                                                                                                          |
| relative positive tolerance of the control supply voltage at AC at 60 Hz | 10 %                                                                                                                                                                           |
| control supply voltage frequency                                         | 50 ... 60 Hz                                                                                                                                                                   |
| relative negative tolerance of the control supply voltage frequency      | -10 %                                                                                                                                                                          |
| relative positive tolerance of the control supply voltage frequency      | 10 %                                                                                                                                                                           |
| control supply current in standby mode rated value                       | 100 mA                                                                                                                                                                         |
| holding current in bypass operation rated value                          | 150 mA                                                                                                                                                                         |
| inrush current by closing the bypass contacts maximum                    | 0.87 A                                                                                                                                                                         |
| inrush current peak at application of control supply voltage maximum     | 43 A                                                                                                                                                                           |
| duration of inrush current peak at application of control supply voltage | 1.6 ms                                                                                                                                                                         |
| design of the overvoltage protection                                     | Varistor                                                                                                                                                                       |
| design of short-circuit protection for control circuit                   | 4 A gG fuse (Icu=1 kA), 6 A quick-acting fuse (Icu=1 kA), C1 miniature circuit breaker (Icu= 600 A), C6 miniature circuit breaker (Icu= 300 A); Is not part of scope of supply |
| <b>Inputs/ Outputs</b>                                                   |                                                                                                                                                                                |
| number of digital inputs                                                 | 4                                                                                                                                                                              |
| • parameterizable                                                        | 4                                                                                                                                                                              |
| • number of digital outputs                                              | 4                                                                                                                                                                              |
| • number of digital outputs parameterizable                              | 3                                                                                                                                                                              |
| • number of digital outputs not parameterizable                          | 1                                                                                                                                                                              |
| digital output version                                                   | 3 normally-open contacts (NO) / 1 changeover contact (CO)                                                                                                                      |
| number of analog outputs                                                 | 1                                                                                                                                                                              |
| switching capacity current of the relay outputs                          |                                                                                                                                                                                |
| • at AC-15 at 250 V rated value                                          | 3 A                                                                                                                                                                            |
| • at DC-13 at 24 V rated value                                           | 1 A                                                                                                                                                                            |
| <b>Installation/ mounting/ dimensions</b>                                |                                                                                                                                                                                |
| mounting position                                                        | Vertical (can be rotated +/- 90° and tilted forward or backward +/- 22.5°)                                                                                                     |
| fastening method                                                         | screw fixing                                                                                                                                                                   |
| height                                                                   | 393 mm                                                                                                                                                                         |
| width                                                                    | 210 mm                                                                                                                                                                         |
| depth                                                                    | 203 mm                                                                                                                                                                         |
| required spacing with side-by-side mounting                              |                                                                                                                                                                                |
| • forwards                                                               | 10 mm                                                                                                                                                                          |
| • backwards                                                              | 0 mm                                                                                                                                                                           |
| • upwards                                                                | 100 mm                                                                                                                                                                         |
| • downwards                                                              | 75 mm                                                                                                                                                                          |
| • at the side                                                            | 5 mm                                                                                                                                                                           |
| weight without packaging                                                 | 10.9 kg                                                                                                                                                                        |
| <b>Connections/ Terminals</b>                                            |                                                                                                                                                                                |
| type of electrical connection                                            |                                                                                                                                                                                |
| • for main current circuit                                               | busbar connection                                                                                                                                                              |
| • for control circuit                                                    | screw-type terminals                                                                                                                                                           |
| width of connection bar maximum                                          | 45 mm                                                                                                                                                                          |
| wire length for thermistor connection                                    |                                                                                                                                                                                |
| • with conductor cross-section = 0.5 mm² maximum                         | 50 m                                                                                                                                                                           |
| • with conductor cross-section = 1.5 mm² maximum                         | 150 m                                                                                                                                                                          |
| • with conductor cross-section = 2.5 mm² maximum                         | 250 m                                                                                                                                                                          |
| type of connectable conductor cross-sections                             |                                                                                                                                                                                |
| • for DIN cable lug for main contacts stranded                           | 2x (50 ... 240 mm²)                                                                                                                                                            |
| • for DIN cable lug for main contacts finely stranded                    | 2x (70 ... 240 mm²)                                                                                                                                                            |
| type of connectable conductor cross-sections                             |                                                                                                                                                                                |
| • for control circuit solid                                              | 1x (0.5 ... 4.0 mm²), 2x (0.5 ... 2.5 mm²)                                                                                                                                     |
| • for control circuit finely stranded with core end processing           | 1x (0.5 ... 2.5 mm²), 2x (0.5 ... 1.5 mm²)                                                                                                                                     |

|                                                                                                                  |                                                                                                                         |
|------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• for AWG cables for control circuit solid</li> </ul>                     | 1x (20 ... 12), 2x (20 ... 14)                                                                                          |
| <b>wire length</b>                                                                                               |                                                                                                                         |
| <ul style="list-style-type: none"> <li>• between soft starter and motor maximum</li> </ul>                       | 800 m                                                                                                                   |
| <ul style="list-style-type: none"> <li>• at the digital inputs at DC maximum</li> </ul>                          | 1 000 m                                                                                                                 |
| <b>tightening torque</b>                                                                                         |                                                                                                                         |
| <ul style="list-style-type: none"> <li>• for main contacts with screw-type terminals</li> </ul>                  | 14 ... 24 N·m                                                                                                           |
| <ul style="list-style-type: none"> <li>• for auxiliary and control contacts with screw-type terminals</li> </ul> | 0.8 ... 1.2 N·m                                                                                                         |
| <b>tightening torque [lbf·in]</b>                                                                                |                                                                                                                         |
| <ul style="list-style-type: none"> <li>• for main contacts with screw-type terminals</li> </ul>                  | 124 ... 210 lbf·in                                                                                                      |
| <ul style="list-style-type: none"> <li>• for auxiliary and control contacts with screw-type terminals</li> </ul> | 7 ... 10.3 lbf·in                                                                                                       |
| <b>Ambient conditions</b>                                                                                        |                                                                                                                         |
| installation altitude at height above sea level maximum                                                          | 2 000 m; Derating as of 1000 m, see catalog                                                                             |
| <b>ambient temperature</b>                                                                                       |                                                                                                                         |
| <ul style="list-style-type: none"> <li>• during operation</li> </ul>                                             | -25 ... +60 °C; Please observe derating at temperatures of 40 °C or above                                               |
| <ul style="list-style-type: none"> <li>• during storage and transport</li> </ul>                                 | -40 ... +80 °C                                                                                                          |
| <b>environmental category</b>                                                                                    |                                                                                                                         |
| <ul style="list-style-type: none"> <li>• during operation according to IEC 60721</li> </ul>                      | 3K6 (no ice formation, only occasional condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6 |
| <ul style="list-style-type: none"> <li>• during storage according to IEC 60721</li> </ul>                        | 1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4                 |
| <ul style="list-style-type: none"> <li>• during transport according to IEC 60721</li> </ul>                      | 2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m)                                                                             |
| <b>Environmental footprint</b>                                                                                   |                                                                                                                         |
| global warming potential [CO2 eq] total                                                                          | 833 kg                                                                                                                  |
| global warming potential [CO2 eq] during manufacturing                                                           | 95.3 kg                                                                                                                 |
| global warming potential [CO2 eq] during sales                                                                   | 2.8 kg                                                                                                                  |
| global warming potential [CO2 eq] during operation                                                               | 756 kg                                                                                                                  |
| global warming potential [CO2 eq] after end of life                                                              | -21 kg                                                                                                                  |
| Siemens Eco Profile (SEP)                                                                                        | Siemens EcoTech                                                                                                         |
| <b>Electromagnetic compatibility</b>                                                                             |                                                                                                                         |
| <b>EMC emitted interference</b>                                                                                  | acc. to IEC 60947-4-2: Class A                                                                                          |
| <b>Communication/ Protocol</b>                                                                                   |                                                                                                                         |
| <b>communication module is supported</b>                                                                         |                                                                                                                         |
| <ul style="list-style-type: none"> <li>• PROFINET standard</li> </ul>                                            | Yes                                                                                                                     |
| <ul style="list-style-type: none"> <li>• PROFINET high-feature</li> </ul>                                        | Yes                                                                                                                     |
| <ul style="list-style-type: none"> <li>• EtherNet/IP</li> </ul>                                                  | Yes                                                                                                                     |
| <ul style="list-style-type: none"> <li>• Modbus RTU</li> </ul>                                                   | Yes                                                                                                                     |
| <ul style="list-style-type: none"> <li>• Modbus TCP</li> </ul>                                                   | Yes                                                                                                                     |
| <ul style="list-style-type: none"> <li>• PROFIBUS</li> </ul>                                                     | Yes                                                                                                                     |
| <b>UL/CSA ratings</b>                                                                                            |                                                                                                                         |
| <b>manufacturer's article number</b>                                                                             |                                                                                                                         |
| <ul style="list-style-type: none"> <li>• of the fuse</li> </ul>                                                  |                                                                                                                         |
| — usable for Standard Faults up to 575/600 V according to UL                                                     | Type: Class J / L, max. 1600 A; Iq = 30 kA                                                                              |
| — usable for High Faults up to 575/600 V according to UL                                                         | Type: Class J / L, max. 1200 A; Iq = 100 kA                                                                             |
| — usable for Standard Faults at inside-delta circuit up to 575/600 V according to UL                             | Type: Class J / L, max. 1600 A; Iq = 30 kA                                                                              |
| — usable for High Faults at inside-delta circuit up to 575/600 V according to UL                                 | Type: Class J / L, max. 1200 A; Iq = 100 kA                                                                             |
| <b>operating power [hp] for 3-phase motors</b>                                                                   |                                                                                                                         |
| <ul style="list-style-type: none"> <li>• at 200/208 V at 50 °C rated value</li> </ul>                            | 150 hp                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 220/230 V at 50 °C rated value</li> </ul>                            | 150 hp                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 460/480 V at 50 °C rated value</li> </ul>                            | 350 hp                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 575/600 V at 50 °C rated value</li> </ul>                            | 450 hp                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 200/208 V at inside-delta circuit at 50 °C rated value</li> </ul>    | 250 hp                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 220/230 V at inside-delta circuit at 50 °C rated value</li> </ul>    | 250 hp                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 460/480 V at inside-delta circuit at 50 °C rated value</li> </ul>    | 600 hp                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 575/600 V at inside-delta circuit at 50 °C rated value</li> </ul>    | 800 hp                                                                                                                  |
| <b>contact rating of auxiliary contacts according to UL</b>                                                      | R300-B300                                                                                                               |
| <b>Electrical Safety</b>                                                                                         |                                                                                                                         |
| <b>protection class IP on the front according to IEC 60529</b>                                                   | IP00; IP20 with cover                                                                                                   |

|                                                                                                                                                        |                                                                                              |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| touch protection on the front according to IEC 60529                                                                                                   | finger-safe, for vertical contact from the front with cover                                  |
| <b>ATEX</b>                                                                                                                                            |                                                                                              |
| Safety Integrity Level (SIL) according to IEC 61508 relating to ATEX                                                                                   | SIL1                                                                                         |
| PFHD with high demand rate according to IEC 61508 relating to ATEX                                                                                     | 5E-7 1/h                                                                                     |
| PFDavg with low demand rate according to IEC 61508 relating to ATEX                                                                                    | 0.008                                                                                        |
| hardware fault tolerance according to IEC 61508 relating to ATEX                                                                                       | 0                                                                                            |
| T1 value for proof test interval or service life according to IEC 61508 relating to ATEX                                                               | 3 a                                                                                          |
| certificate of suitability <ul style="list-style-type: none"> <li>• ATEX</li> <li>• IECEx</li> <li>• according to ATEX directive 2014/34/EU</li> </ul> | Yes<br>Yes<br>BVS 18 ATEX F 003 X                                                            |
| type of protection according to ATEX directive 2014/34/EU                                                                                              | II (2)G [Ex eb Gb] [Ex db Gb] [Ex pxb Gb], II (2)D [Ex tb Db] [Ex pxb Db], I (M2) [Ex db Mb] |

#### Approvals Certificates

|                          |     |
|--------------------------|-----|
| General Product Approval | EMV |
|--------------------------|-----|



|     |                                |                   |                      |
|-----|--------------------------------|-------------------|----------------------|
| EMV | For use in hazardous locations | Test Certificates | Maritime application |
|-----|--------------------------------|-------------------|----------------------|

[KC](#)



[Type Test Certificates/Test Report](#)



|                      |       |             |
|----------------------|-------|-------------|
| Maritime application | other | Environment |
|----------------------|-------|-------------|



[Confirmation](#)

Siemens EcoTech



[Environmental Confirmations](#)

#### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5547-6HA16>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5547-6HA16>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5547-6HA16>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5547-6HA16&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5547-6HA16&lang=en)

Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5547-6HA16/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5547-6HA16&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>





