



Complete unit, knob, L-R 22 mm plastic round selector switch 2 switch positions L-R 90DEG, V position latching non-illuminated screw terminal, 1 NO with holder black

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Selector switch
design of the product	Complete unit
product type designation	3SB6
product line	Plastic, metalized, matt, 22 mm
shape of the enclosure front	round
principle of operation of the actuating element	maintained
product extension optional light source	No
color of the actuating element	black
number of switching positions	2
product component front ring	No
material of the front ring	metalized
color of the front ring	silver
product component light source	No
protection class IP	IP65
mechanical service life (operating cycles) typical	300 000
electrical endurance (operating cycles) typical	3 000 000
Substance Prohibittance (Date)	03/01/2017
Weight	39.54 g
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	1
number of CO contacts for auxiliary contacts	0
ambient temperature	
• during operation	-25 ... +75 °C
• during storage	-40 ... +80 °C
fastening method	screw fixing
mounting diameter	22 mm
mounting height	46.5 mm
installation width	30 mm

Approvals Certificates	
General Product Approval	other



[Confirmation](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6130-2AA10-1BA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6130-2AA10-1BA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6130-2AA10-1BA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6130-2AA10-1BA0&lang=en



last modified:

4/3/2025 