



Contact block for position switch 3SE51/52 1 NO/2 NC quick action contact

|                                                                   |                                                      |
|-------------------------------------------------------------------|------------------------------------------------------|
| product brand name                                                | SIRIUS                                               |
| product designation                                               | contact                                              |
| product type designation                                          | 3SE5                                                 |
| <b>General technical data</b>                                     |                                                      |
| product function positive opening                                 | Yes                                                  |
| insulation voltage rated value                                    | 400 V                                                |
| degree of pollution                                               | class 3                                              |
| surge voltage resistance rated value                              | 6 kV                                                 |
| protection class IP                                               | IP00                                                 |
| shock resistance                                                  |                                                      |
| • according to IEC 60068-2-27                                     | 30g / 11 ms                                          |
| vibration resistance                                              |                                                      |
| • according to IEC 60068-2-6                                      | 0.35 mm/5g                                           |
| mechanical service life (operating cycles) typical                | 15 000 000                                           |
| electrical endurance (operating cycles) at AC-15 at 230 V typical | 100 000                                              |
| thermal current                                                   | 10 A                                                 |
| reference code according to IEC 81346-2                           | S                                                    |
| continuous current of the C characteristic MCB                    | 1 A; for a short-circuit current smaller than 400 A  |
| continuous current of the quick DIAZED fuse link                  | 10 A; for a short-circuit current smaller than 400 A |
| continuous current of the DIAZED fuse link gG                     | 6 A                                                  |
| active principle                                                  | mechanical                                           |
| repeat accuracy                                                   | 0.1 mm                                               |
| Substance Prohibitance (Date)                                     | 07/01/2006                                           |
| Weight                                                            | 0.026 kg                                             |
| width of the sensor                                               | 25 mm                                                |
| <b>Ambient conditions</b>                                         |                                                      |
| ambient temperature                                               |                                                      |
| • during operation                                                | -25 ... +85 °C                                       |
| • during storage                                                  | -40 ... +90 °C                                       |
| explosion protection category for dust                            | none                                                 |
| <b>Main circuit</b>                                               |                                                      |
| operating frequency rated value                                   | 50 ... 60 Hz                                         |
| number of NC contacts for auxiliary contacts                      | 2                                                    |
| number of NO contacts for auxiliary contacts                      | 1                                                    |
| operational current at AC-15                                      |                                                      |
| • at 24 V rated value                                             | 6 A                                                  |
| • at 125 V rated value                                            | 6 A                                                  |
| • at 240 V rated value                                            | 6 A                                                  |
| • at 400 V rated value                                            | 4 A                                                  |

|                                                          |                                                                       |
|----------------------------------------------------------|-----------------------------------------------------------------------|
| <b>operational current at DC-13</b>                      |                                                                       |
| • at 24 V rated value                                    | 3 A                                                                   |
| • at 125 V rated value                                   | 0.55 A                                                                |
| • at 250 V rated value                                   | 0.27 A                                                                |
| • at 400 V rated value                                   | 0.12 A                                                                |
| <b>Enclosure</b>                                         |                                                                       |
| <b>coating of the enclosure</b>                          | Other types                                                           |
| <b>Drive Head</b>                                        |                                                                       |
| <b>design of the switching function</b>                  | positive opening                                                      |
| <b>circuit principle</b>                                 | snap-action contacts                                                  |
| number of switching contacts safety-related              | 2                                                                     |
| <b>Installation/ mounting/ dimensions</b>                |                                                                       |
| <b>mounting position</b>                                 | any                                                                   |
| <b>fastening method</b>                                  | snap-on mounting                                                      |
| <b>Connections/ Terminals</b>                            |                                                                       |
| <b>type of electrical connection</b>                     | screw terminal                                                        |
| <b>type of connectable conductor cross-sections</b>      |                                                                       |
| • solid                                                  | 1x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.5 ... 0.75 mm <sup>2</sup> ) |
| • finely stranded with core end processing               | 1x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.5 ... 0.75 mm <sup>2</sup> ) |
| • for AWG cables solid                                   | 1x (20 ... 16), 2x (20 ... 18)                                        |
| • for AWG cables stranded                                | 1x (20 ... 16), 2x (20 ... 18)                                        |
| design of the interface for safety-related communication | without                                                               |
| <b>Communication/ Protocol</b>                           |                                                                       |
| <b>design of the interface</b>                           | without                                                               |
| <b>Approvals Certificates</b>                            |                                                                       |
| <b>General Product Approval</b>                          |                                                                       |



[KC](#)



| Functional Safety | Test Certificates | other | Environment |
|-------------------|-------------------|-------|-------------|
|-------------------|-------------------|-------|-------------|



[Type Test Certificates/Test Report](#)



[Confirmation](#)

[Environmental Confirmations](#)

#### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SE5000-0LA00>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SE5000-0LA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SE5000-0LA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SE5000-0LA00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SE5000-0LA00&lang=en)



---

last modified:

4/2/2025 