



Figure similar

SETRON, cylindrical fuse link, 22x58 mm, 80 A, gG, Un AC: 500 V

Model	
product brand name	SETRON
product designation	Cylindrical fuse link
General technical data	
operating class of the fuse link	gG
type of voltage of the operating voltage	AC
supply voltage at DC	250 V
Dissipation	
power loss [W]	7.5 W
power loss [W] for rated value of the current at AC in hot operating state per pole	8 W
Main circuit	
operational current rated value	80 A
Product details	
product component striker	No
Mechanical Design	
mounting position	Any, preferably vertical
net weight	53 g
Approvals Certificates	
General Product Approval	other



[Confirmation](#)

[Miscellaneous](#)[Confirmation](#)

Environment
Environmental Confirmations

Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NW6224-1

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NW6224-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW6224-1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

7/13/2023 

