

Switch disconnector with fuse 250 A, Size 3, 3-pole for LV HRC fuse Sz. 0 and 1  
Front operating mechanism center Basic unit without handle flat terminal



Model	
product brand name	SENTRON
product designation	3KF switch disconnector with fuses
design of the product	3KF switch disconnector with fuses
product variations	3KF NH
design of the actuating element	without
design of handle	Without
direction of actuation	from the front
type of the driving mechanism motor drive	No
number of poles	3
size of disconnecting link	1 and 0
size of switch disconnector	3
size of fuse link	NH0, NH1
mechanical service life (operating cycles) typical	10 000
electrical endurance (operating cycles)	
• at AC-23 A at 440 V	5 000
• at AC-23 A at 690 V	4 000
• at DC-23 A at 440 V	1 000
I <sub>2t</sub> value	
• with closed switch for combination switch + fuse at 500 V maximum	437 000 A <sup>2</sup> ·s
• with closed switch for combination switch + fuse at 400 V maximum	437 000 A <sup>2</sup> ·s
• with closed switch at 690 V for combination switch + gG fuse maximum	490 100 A <sup>2</sup> ·s
• of the fuse at 500 V maximum permissible	1 500 000 A <sup>2</sup> ·s
• of the gG fuse at 690 V maximum permissible	940 000 A <sup>2</sup> ·s
• of the aM fuse at 690 V maximum permissible	1 400 000 A <sup>2</sup> ·s
position of the switch operating mechanism	center left
fuse system	LV HRC fuse
overvoltage category	IV
operating voltage with current paths in series	
• with degree of pollution 2 at DC rated value	440 / 3
• with degree of pollution 3 at DC rated value	440 / 3
surge voltage resistance rated value	12 kV
Supply voltage	
operating voltage at AC rated value maximum	690 V
Protection class	
protection class IP	IP00
protection class IP	
• with closed switch with cover or cable lug cover	IP20

- on the front

IP00

**Dissipation****power loss [W]**

- with conventional rated thermal current per pole 15 W
- with conventional rated thermal current per device 45 W
- with conventional rated thermal current without fuse per pole 15 W
- with conventional rated thermal current without fuse per device 45 W
- for rated value of the current at AC in hot operating state per pole 15 W
- of the fuse per fuse maximum 25.5 W

**Main circuit**

operating power at AC-23 A at 500 V rated value	160 kW
operational current rated value	250 A

**Auxiliary circuit**

number of connected NC contacts for auxiliary contacts	0
number of connected NO contacts for auxiliary contacts	0
number of connected CO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	0
number of NC contacts for auxiliary contacts	8
number of NO contacts for auxiliary contacts	8
suitability for use main switch	Yes
suitability for use switch disconnector	Yes
suitability for use EMERGENCY OFF switch	Yes
suitability for use safety switch	Yes
suitability for use maintenance/repair switch	Yes
product feature interlock	No
product function phase failure monitoring	No
product component	
• voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No
product feature sealable	Yes
product extension auxiliary switch	Yes
product extension optional	
• locking capability	Yes
• motor drive	No
• fuse monitoring	Yes
product function	
• fuse monitoring	No
• overvoltage protection monitoring	No

**Short circuit**

short-circuit current making capacity (Icm) for switch disconnector at 690 V AC/440 V DC without fuse link rated value minimum	13.6 kA
conditional short-circuit current with line-side fuse protection	
• at 500 V by gG fuse rated value	100 kA
• at 690 V by gG fuse rated value	100 kA

**Connections**

arrangement of electrical connectors for main current circuit	Top and bottom
tightening torque with screw-type terminals	
• minimum	30 N·m
• maximum	44 N·m
type of connectable conductor cross-sections for aluminum conductor stranded with lug	1x (6 ... 240 mm <sup>2</sup> ), 2x (6 ... 120 mm <sup>2</sup> )
type of connectable conductor cross-sections	
• for copper busbar	1x (25 x 3 mm <sup>2</sup> )
type of connectable conductor cross-sections for copper conductor	
• stranded with lug according to DIN 46234	1x (6 ... 240 mm <sup>2</sup> ), 2x (6 ... 120 mm <sup>2</sup> )
• stranded with lug according to DIN 46235	1x (6 ... 240 mm <sup>2</sup> ), 2x (6 ... 120 mm <sup>2</sup> )

type of electrical connection for main current circuit	flat connector
<b>Mechanical Design</b>	
height	207 mm
width	247.7 mm
depth	188.5 mm
fastening method	floor mounting
fastening method	
• 4-hole front mounting	No
• front mounting with central attachment	No
• rail mounting	No
mounting position	any
net weight	4 250 g
<b>Environmental conditions</b>	
ambient temperature during operation	
• minimum	-25 °C
• maximum	70 °C
ambient temperature during storage	
• minimum	-50 °C
• maximum	80 °C

#### Approvals Certificates

##### General Product Approval



[Confirmation](#)







[Miscellaneous](#)

General Product Approval	Test Certificates	Marine / Shipping	other	Environment
	<a href="#">Type Test Certificates/Test Report</a>		<a href="#">Confirmation</a>	<a href="#">Miscellaneous</a>

Environment
<a href="#">Environmental Confirmations</a>

Further information
Information on the packaging <a href="https://support.industry.siemens.com/cs/ww/en/view/109813875">https://support.industry.siemens.com/cs/ww/en/view/109813875</a>
Information- and Downloadcenter (Catalogs, Brochures,...) <a href="http://www.siemens.com/lowvoltage/catalogs">http://www.siemens.com/lowvoltage/catalogs</a>
Industry Mall (Online ordering system) <a href="https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KF3325-0MF11">https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KF3325-0MF11</a>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) <a href="https://support.industry.siemens.com/cs/ww/en/ps/3KF3325-0MF11">https://support.industry.siemens.com/cs/ww/en/ps/3KF3325-0MF11</a>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) <a href="http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KF3325-0MF11">http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KF3325-0MF11</a>
CAx-Online-Generator <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
Tender specifications <a href="http://www.siemens.com/specifications">http://www.siemens.com/specifications</a>





---

last modified:

8/2/2022

