

## Data sheet for Active Line Modules

Article No. : 6SL3130-7TE28-0AA3

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :



Figure similar

Electrical data	
<b>Input</b>	
Number of phases	3 AC
Line voltage	342 ... 528 V
Line frequency	47 ... 63 Hz
Short-circuit strength <sup>1)</sup>	65 kA
<b>Line power factor</b>	
<b>in Active mode</b>	
Fundamental power factor cos phi <sub>1</sub> <sup>2)</sup>	1
Total	1
<b>in Smart Mode</b>	
Fundamental power factor, minimal	.96
Total	0.65 ... 0.90
Overvoltage category	Class III
<b>DC link voltage <sup>3)</sup></b>	
at 380 V ... 400 V AC, factory setting	600 V
at 400 V ... 415 V AC, factory setting	625 V
DC-link voltage	1.35 x line voltage (Smart Mode)
Electronics power supply with DC	24 V (-15 % / 20 %)

Connections	
<b>Line side</b>	
Design	M8 bolt (X1)
Conductor cross-section	2.50 ... 120.00 mm <sup>2</sup> (AWG 14 ... AWG - 3) (Alternatively 2 x 50 mm <sup>2</sup> )
PE conductor	M8 Screw
<b>Line length, max.</b>	
Shielded	1,000 m (3,280.84 ft)
Unshielded	1,500 m (4,921.26 ft)

Mechanical data	
<b>Dimensions</b>	
Width	300 mm (11.81 in)
Height	629 mm (24.76 in)
Depth	270 mm (10.63 in)
Degree of protection	IP20 / UL open type
Net weight	23.0 kg (50.71 lb)
Type of construction	Booksize

Rated data	
<b>Infeed power</b>	
Rated value	80 kW (100 hp)
for S6 duty	106 kW
Maximum	131 kW
<b>Regenerative feedback power</b>	
Rated value	80 kW (100 hp)
for S6 duty	106 kW
Maximum	131 kW
<b>DC-link current</b>	
at 600 V DC	134 A
for S6 duty	176 A
Maximum	218 A
<b>Input current</b>	
at 380 V AC 3-phase	128 A
at 400 V AC 3-phase	122 A
at 480 V AC 3-phase	102 A
at 400 V S6 duty	161 A
at 400 V, maximum	200 A
Current requirement at 24 V DC, maximum	2.0 A
<b>Ampacity of the busbars</b>	
for electronics power supply at 24 V DC	20 A
for DC-link connection	200 A
<b>DC link capacitance</b>	
of the Active Line Module	2,820 µF
of the drive system, maximum	20,000 µF

General technical specifications	
Sound pressure level	73 dB
Losses <sup>10)</sup>	1.38 kW

Ambient conditions	
Ambient temperature in operation	0 ... 40 °C (32 ... 104 °F)
Cooling air throughput	0.144 m³/s (5.085 ft³/s)
Installation altitude	1,000 m (3,280.84 ft)
Type of cooling <sup>11)</sup>	Internal air cooling
RI suppression	Active Line Module + Active Interface Module: Category C3 according to EN 61800-3 up to 350 m (1148 ft) total cable length. With line filter: Category C2 according to EN 61800-3 up to 350 m (1148 ft) total cable length. Category C3 according to EN 61800-3 from 350 m to 1000 m (1148 ... 3281 ft) total cable length.

Standards	
Compliance with standards	CE, cULus

## Data sheet for Active Line Modules

Article No. : 6SL3130-7TE28-0AA3

<sup>1)</sup> in conjunction with the recommended Class J fuse, or circuit breaker according to UL489 / CSA 22.2 No. 5-02

<sup>2)</sup> Factory setting can be altered by inputting a reactive current setpoint (Active Mode)

<sup>3)</sup> In Active Mode, the DC link voltage is regulated and can be adjusted as a voltage decoupled from the line voltage. In Smart Mode, the DC link voltage is kept in proportion to the line voltage at the mean rectified line voltage value. For line voltages of 416 ... 480 V AC, Active Mode can also be selected if the connected motors are suitable for > 650 V DC.

<sup>10)</sup> Power loss of the Active Line Module with rated power including losses of the 24 V DC electronics power supply

<sup>11)</sup> Power units with intensified air cooling thanks to integrated fan