

6ES7414-2XG03-0AB0**CPU414-2, MPI/DP, 256KB****Technical data**SIMATIC S7-400, CPU 414-2 256 KB WORKING MEMORY (128 KB CODE, 128 KB DATA)
1. INTERFACE MPI/DP 12 MBIT/S 2. INTERFACE DP

General information

Product function	
• Isochronous mode	Yes

CiR - Configuration in RUN

CiR synchronization time, basic load	100 ms
CiR synchronization time, time per I/O byte	120 µs

Supply voltage

Rated value (DC)	Power supply via system power supply
------------------	--------------------------------------

Input current

from backplane bus 5 V DC, typ.	1.5 A
from backplane bus 5 V DC, max.	1.6 A
from backplane bus 24 V DC, max.	300 mA; Total current consumption of the components connected to the MPI/DP interfaces, but no more than 150 mA per interface

Power loss

Power loss, typ.	7.5 W
------------------	-------

Memory

Type of memory	RAM
----------------	-----

Work memory

• integrated	256 kbyte
• integrated (for program)	128 kbyte
• integrated (for data)	128 kbyte
• expandable	No

Load memory

• expandable FEPRM	Yes; with Memory Card (FLASH)
• expandable FEPRM, max.	64 Mbyte
• integrated RAM, max.	256 kbyte
• expandable RAM	Yes; with Memory Card (RAM)
• expandable RAM, max.	64 Mbyte

Backup

• present	Yes
• with battery	Yes; all data
• without battery	No

Battery

Backup battery	
• Backup current, typ.	40 µA
• Backup current, max.	380 µA
• Feeding of external backup voltage to CPU	5 V DC to 15 V DC

CPU processing times

for bit operations, typ.	0.1 µs
for word operations, typ.	0.1 µs
for fixed point arithmetic, typ.	0.1 µs
for floating point arithmetic, typ.	0.6 µs

CPU-blocks

DB	
• Number, max.	4 095; DB 0 reserved
• Size, max.	64 kbyte
FB	
• Number, max.	2 048
• Size, max.	64 kbyte
FC	
• Number, max.	2 048
• Size, max.	64 kbyte
OB	
• Number, max.	see instruction list
• Size, max.	64 kbyte
• Number of time alarm OBs	4
• Number of delay alarm OBs	4
• Number of cyclic interrupt OBs	4
• Number of process alarm OBs	4
Nesting depth	
• per priority class	24
• additional within an error OB	2

Counters, timers and their retentivity

S7 counter	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	Z 0 to Z 7
Counting range	
— lower limit	1
— upper limit	999
IEC counter	
• present	Yes
• Type	SFB
S7 times	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	No retentivity
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB

Data areas and their retentivity

retentive data area in total	Total working and load memory (with backup battery)
Flag	
• Number, max.	8 kbyte
• Retentivity available	Yes; From MB 0 to MB 8 191
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte

Address area

I/O address area	
• Inputs	8 kbyte
• Outputs	8 kbyte
Process image	
• Inputs, adjustable	8 kbyte; adjustable at the expense of the code area of the RAM
• Outputs, adjustable	8 kbyte; adjustable at the expense of the code area of the RAM
• Inputs, default	256 byte
• Outputs, default	256 byte
• consistent data, max.	244 byte
• Access to consistent data in process image	Yes
Subprocess images	
• Number of subprocess images, max.	8
Digital channels	
• Inputs	65 536
— of which central	65 536
• Outputs	65 536
— of which central	65 536
Analog channels	
• Inputs	4 096
— of which central	4 096
• Outputs	4 096
— of which central	4 096

Hardware configuration

Number of expansion units, max.	21; of which 6 ER with K-bus
connectable OPs	31 without message processing, 8 with message processing
Multicomputing	Yes; 4 CPUs max. (with UR1 or UR2)
Interface modules	
• Number of connectable IMs (total), max.	6
• Number of connectable IM 460s, max.	6
• Number of connectable IM 463s, max.	4; IM 463-2
Number of DP masters	
• integrated	2
• via CP	10
• via IM 467	4
• Mixed mode IM + CP permitted	No; IM 467 cannot be used jointly with CP 443-5 Ext.
• via interface module	0
• Number of pluggable S5 modules (via adapter capsule in central device), max.	6
Number of operable FMs and CPs (recommended)	
• FM	32; Limited by number of slots and number of connections
• CP, PTP	32; limited by number of slots
• CP, LAN	32; limited by number of connections

• PROFIBUS and Ethernet CPs	14; incl. CP 443-5 Ext. and IM 467
Slots	
• required slots	1
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Resolution	1 ms
Operating hours counter	
• Number	8
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• to DP, master	Yes
• to DP, slave	Yes
• in AS, master	Yes
• in AS, slave	Yes
1. Interface	
Interface type	MPI/PROFIBUS DP
Isolated	Yes
Interface types	
• RS 485	Yes
Protocols	
• MPI	Yes
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
MPI	
• Number of connections	32
• Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
PROFIBUS DP master	
• Number of connections, max.	16
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
PROFIBUS DP slave	
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— PG/OP communication	Yes; with interface active
— Routing	Yes; with interface active
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
2. Interface	
Interface type	PROFIBUS DP
Isolated	Yes
Number of connection resources	16
Interface types	
• RS 485	Yes
Protocols	
• PROFIBUS DP master	Yes

• PROFIBUS DP slave	Yes
PROFIBUS DP master	
• Number of connections, max.	16
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	96
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Address area	
— Inputs, max.	6 kbyte
— Outputs, max.	6 kbyte
User data per DP slave	
— Inputs, max.	128 byte
— Outputs, max.	128 byte
PROFIBUS DP slave	
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— Routing	Yes; with interface active
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
Protocols	
SIMATIC communication	
• S7 routing	Yes
Isochronous mode	
Equidistance	Yes
User data per isochronous slave, max.	128 byte
shortest clock pulse	5 ms; 2.5 ms without using the SFCs 126 / 127
Communication functions	
PG/OP communication	Yes
Global data communication	
• supported	Yes
• Number of GD packets, transmitter, max.	8
• Number of GD packets, receiver, max.	16
• Size of GD packets, max.	64 byte
S7 basic communication	
• supported	Yes
• User data per job, max.	76 byte
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	64 kbyte
S5 compatible communication	
• supported	Yes; via CP and FC AG_SEND and FC AG_RECV
• User data per job, max.	8 kbyte
Standard communication (FMS)	
• supported	Yes; Via CP and loadable FB
Number of connections	
• overall	32; of which one is reserved for PG and OP
• usable for PG communication	
— reserved for PG communication	1
— adjustable for PG communication, max.	0
• usable for OP communication	
— reserved for OP communication	1
— adjustable for OP communication, max.	0
• usable for S7 basic communication	
— reserved for S7 basic communication	0
— adjustable for S7 basic communication, max.	0
• usable for S7 communication	
— reserved for S7 communication	0
— adjustable for S7 communication, max.	0
• usable for routing	
— reserved for routing	0
— adjustable for routing, max.	0
S7 message functions	
Number of login stations for message functions, max.	8

Symbol-related messages	Yes
Program alarms	Yes
Alarm 8-blocks	Yes
Process control messages	Yes
Test commissioning functions	
Status block	Yes
Single step	Yes
Number of breakpoints	4
Status/control	
• Status/control variable	Yes
Forcing	
• Forcing	Yes
Diagnostic buffer	
• present	Yes
• Number of entries, max.	400
— adjustable	Yes
Configuration	
Configuration software	
• STEP 7	Yes
Programming	
• Nesting levels	8
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
Know-how protection	
• User program protection/password protection	Yes
Dimensions	
Width	25 mm
Height	290 mm
Depth	219 mm
Weights	
Weight, approx.	720 g
last modified:	12/10/2020

Last changes: 12/10/2020