

SECTION 3x 1600 A SANS COMM

Model	
product brand name	SENTRON
product designation	Switch disconnecter
design of the product	Basic versions without handle
design of the load switch strip form	No
type of the driving mechanism motor drive	No
General technical data	
number of poles	3
type of device	fixed mounting
mechanical service life (operating cycles) typical	12 000
operating voltage at DC rated value	440 V
Protection class	
protection class IP	IP00
Dissipation	
power loss [W] for rated value of the current at AC in hot operating state per pole	38.3 W
Suitability	
suitability for use EMERGENCY OFF switch	Yes
Connections	
type of electrical connection	Busbar connection
• for main current circuit	flat connector
Mechanical Design	
height	306 mm
width	356 mm
depth	186 mm
fastening method	floor mounting
Net Weight	18 kg
Environmental conditions	
ambient temperature during operation	
• minimum	-20 °C
• maximum	45 °C
ambient temperature during storage minimum	-25 °C
Further information	

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KA7154-3AA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3KA7154-3AA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KA7154-3AA00

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>

