

Siemens  
EcoTech



circuit breaker 3VA2 IEC Frame 100 breaking capacity class L Icu=150 kA @ 415 V 3-pole, line protection ETU550, LSI, In=25 A overload protection Ir=10 A...25 A short-circuit protection I<sub>sd</sub>=0.6..10x I<sub>n</sub>, I<sub>i</sub>=1.5..12x I<sub>n</sub> neutral conductor protection optionally with external current transformer, up to 160% terminal connection



| Model                                                                                                 |                             |
|-------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                    | SENTRON                     |
| product designation                                                                                   | Molded case circuit breaker |
| design of the product                                                                                 | Line protection             |
| design of the overcurrent release                                                                     | ETU550                      |
| protection function of the overcurrent release                                                        | LSI                         |
| number of poles                                                                                       | 3                           |
| General technical data                                                                                |                             |
| insulation voltage / rated value                                                                      | 800 V                       |
| operating voltage / at AC / rated value                                                               | 690 V                       |
| power loss [W] / maximum                                                                              | 0.5 W                       |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole           | 0.17 W                      |
| mechanical service life (operating cycles) / typical                                                  | 25 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                      | 15 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 690 V                                          | 10 500                      |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof | Yes                         |
| ground-fault monitoring version                                                                       | Without                     |
| product function                                                                                      |                             |
| • communication function                                                                              | Yes                         |
| • other measurement function                                                                          | No                          |
| Net Weight                                                                                            | 2.5 kg                      |
| Current                                                                                               |                             |
| operational current                                                                                   |                             |
| • at 40 °C                                                                                            | 25 A                        |
| • at 45 °C                                                                                            | 25 A                        |
| • at 50 °C                                                                                            | 25 A                        |
| • at 55 °C                                                                                            | 25 A                        |
| • at 60 °C                                                                                            | 25 A                        |
| • at 65 °C                                                                                            | 25 A                        |
| • at 70 °C                                                                                            | 25 A                        |
| Switching capacity according to IEC 60947                                                             |                             |
| switching capacity class of the circuit breaker                                                       | L                           |
| maximum short-circuit current breaking capacity (I <sub>cu</sub> )                                    |                             |
| • at 240 V                                                                                            | 200 kA                      |
| • at 415 V                                                                                            | 150 kA                      |
| • at 440 V                                                                                            | 150 kA                      |

|                                                                                                                                              |         |
|----------------------------------------------------------------------------------------------------------------------------------------------|---------|
| <ul style="list-style-type: none"> <li>• at 500 V</li> <li>• at 690 V</li> </ul>                                                             | 100 kA  |
| operating short-circuit current breaking capacity (Ics)                                                                                      | 25 kA   |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul> | 200 kA  |
|                                                                                                                                              | 150 kA  |
|                                                                                                                                              | 150 kA  |
|                                                                                                                                              | 100 kA  |
|                                                                                                                                              | 18 kA   |
| short-circuit current making capacity (Icm)                                                                                                  |         |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul> | 440 kA  |
|                                                                                                                                              | 330 kA  |
|                                                                                                                                              | 330 kA  |
|                                                                                                                                              | 220 kA  |
|                                                                                                                                              | 52.5 kA |

#### Adjustable parameters

|                                                                                          |                             |
|------------------------------------------------------------------------------------------|-----------------------------|
| product feature / for L-tripping / can be switched on/off                                | No                          |
| adjustable response value setting current (Ir) / of the L-trip / with I2t characteristic |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>           | 10 A                        |
|                                                                                          | 25 A                        |
| adjustable response value delay time (tr) / for L-tripping / with I2t characteristic     |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>           | 0.5 s                       |
|                                                                                          | 25 s                        |
| adjustable response value setting current (Isd) / of S-trip / with I0t characteristic    |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>           | 15 A                        |
|                                                                                          | 250 A                       |
| adjustable response value setting current (Isd) / of S-trip / with I2t characteristic    |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>           | 15 A                        |
|                                                                                          | 250 A                       |
| adjustable response value delay time (tsd) / for S-tripping / with I0t characteristic    |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>           | 0.05 s                      |
|                                                                                          | 0.5 s                       |
| adjustable response value delay time (tsd) / for S-tripping / with I2t characteristic    |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>           | 0.05 s                      |
|                                                                                          | 0.5 s                       |
| adjustable response value setting current (Ii) / for I-tripping                          |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>           | 38 A                        |
|                                                                                          | 300 A                       |
| adjustable setting current (InN) / for N-tripping                                        |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>           | 10 A                        |
|                                                                                          | 40 A                        |
| design of the N-conductor protection                                                     | adjustable OFF; 40% to 160% |
| product function / grounding protection                                                  | No                          |

#### Mechanical Design

|                                                                                                                               |                   |
|-------------------------------------------------------------------------------------------------------------------------------|-------------------|
| product component                                                                                                             |                   |
| <ul style="list-style-type: none"> <li>• undervoltage release</li> <li>• voltage trigger</li> <li>• trip indicator</li> </ul> | No                |
|                                                                                                                               | No                |
|                                                                                                                               | No                |
| height [in]                                                                                                                   | 7.13 in           |
| height                                                                                                                        | 181 mm            |
| width [in]                                                                                                                    | 4.13 in           |
| type of connectable conductor cross-sections / of the round conductor terminal / stranded                                     | 1 x (6 - 120 mm²) |
| width                                                                                                                         | 105 mm            |
| depth [in]                                                                                                                    | 3.39 in           |
| depth                                                                                                                         | 86 mm             |

#### Connections

|                                                                 |                |
|-----------------------------------------------------------------|----------------|
| arrangement of electrical connectors / for main current circuit | Front terminal |
|-----------------------------------------------------------------|----------------|

|                                                                                       |                           |
|---------------------------------------------------------------------------------------|---------------------------|
| type of electrical connection / for main current circuit                              | double-sided box terminal |
| design of the surface / of the connections / on the top of the switch (N, 1, 3, 5)    | tin                       |
| design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6) | tin                       |

#### Auxiliary circuit

|                                                |   |
|------------------------------------------------|---|
| number of CO contacts / for auxiliary contacts | 0 |
|------------------------------------------------|---|

#### Accessories

|                                            |     |
|--------------------------------------------|-----|
| product extension / optional / motor drive | Yes |
|--------------------------------------------|-----|

#### Environmental conditions

|                                    |        |
|------------------------------------|--------|
| protection class IP / on the front | IP40   |
| ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |
| • during storage / minimum         | -40 °C |
| • during storage / maximum         | 80 °C  |

#### Environmental footprint

|                                                          |                 |
|----------------------------------------------------------|-----------------|
| Global Warming Potential [CO2 eq] / total                | 61.814 kg       |
| Global Warming Potential [CO2 eq] / during manufacturing | 14.6 kg         |
| Global Warming Potential [CO2 eq] / during operation     | 48.9 kg         |
| Global Warming Potential [CO2 eq] / after end of life    | -2.2 kg         |
| Siemens Eco Profile (SEP)                                | Siemens EcoTech |
| reference code / according to IEC 81346-2                | Q               |

#### Approvals / Certificates

##### General Product Approval



[Confirmation](#)



[Miscellaneous](#)

| General Product Approval | EMV | Test Certificates | Marine / Shipping |
|--------------------------|-----|-------------------|-------------------|
|--------------------------|-----|-------------------|-------------------|



[Type Test Certificates/Test Report](#)

[Miscellaneous](#)

[Special Test Certificate](#)



| Marine / Shipping | other |
|-------------------|-------|
|-------------------|-------|



[CCS \(China Classification Society\)](#)

[Miscellaneous](#)

| other | Dangerous goods | Environment |
|-------|-----------------|-------------|
|-------|-----------------|-------------|

[Confirmation](#)

[Miscellaneous](#)

[Transport Information](#)



Siemens EcoTech



[Environmental Confirmations](#)

#### Environment

[Environmental Confirmations](#)

## Further information

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2025-8JP36-0AA0>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2025-8JP36-0AA0>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2025-8JP36-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2025-8JP36-0AA0)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>





