



Figure similar

SIPLUS G120 CU240E-2 PN based on 6SL3244-0BB12-1FA0 with conformal coating, -20...+55 °C, Control Unit CU240E-2 PN E-type with Safety Integrated STO PROFINET 6 DI, 3 DQ, 2 AI, 2 AQ, max. 1F-DI PTC/KTY interface USB and SD/MMC interface degree of protection IP20 without Power Module

General information	
Product type designation	CU240E-2 PN
Product function	<ul style="list-style-type: none"> • V/f control with linear/square parameterization capability • V/f control with ECO mode linear/square • V/f control with flux current control • Vector control with encoder • Vector control without encoder
Supply voltage	<ul style="list-style-type: none"> Operating voltage from Power Module Operating voltage from external power supply, min. Operating voltage from external power supply, max.
Input current	Current consumption, max.
Power loss	Power loss, max.
Digital inputs	<ul style="list-style-type: none"> Number of digital inputs With fail-safe
Digital outputs	<ul style="list-style-type: none"> Number of digital outputs As transistor As relay change-over contact
Analog inputs	<ul style="list-style-type: none"> Number of analog inputs Type of analog input Remark Input voltage with signal "0" to "1" Input voltage with signal "1" to "0"
Analog outputs	Number of analog outputs
Analog value generation for the inputs	
Interfaces	<ul style="list-style-type: none"> Number of PROFINET interfaces Number of RS 485 interfaces

Protocols	
PROFIBUS	No
Isolation	
Type of protective insulation	PELV according to EN 50178, safe disconnection from the mains by double/reinforced isolation
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
Certificate of suitability	CE / TÜV
Ambient conditions	
Ambient temperature during operation	<ul style="list-style-type: none"> • min. • max. • min. [°F] • max. [°F] • Remark <p>-20 °C; = Tmin 55 °C; = Tmax -4 °F 131 °F</p> <p>A derating of 3 K/1 000 m has to be applied to the Control Units from an installation altitude of 1 000 m above sea level</p>
Ambient temperature during storage/transportation	<ul style="list-style-type: none"> • Storage, min. • Storage, max. • Storage, min. [°F] • Storage, max. [°F] <p>-40 °C 70 °C -40 °F 158 °F</p>
Relative humidity	<ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. <p>100 %; RH incl. condensation/frost (no commissioning under condensation conditions)</p>
Resistance	
Use in stationary industrial systems	<ul style="list-style-type: none"> — to biologically active substances according to EN 60721-3-3 — to chemically active substances according to EN 60721-3-3 — to mechanically active substances according to EN 60721-3-3 <p>Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request</p> <p>Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *</p> <p>No</p>
Usage in industrial process technology	<ul style="list-style-type: none"> — Against chemically active substances acc. to EN 60654-4 — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 <p>Yes; Class 3 (excluding trichlorethylene)</p> <p>Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)</p>
Remark	<ul style="list-style-type: none"> — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 <p>* The supplied plug covers must remain in place over the unused interfaces during operation!</p>
Conformal coating	<ul style="list-style-type: none"> • Coatings for printed circuit board assemblies acc. to EN 61086 • Military testing according to MIL-I-46058C, Amendment 7 • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A <p>Yes; Class 2 for high reliability</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p>
connection method	
Type of electrical connection for signal line	<ul style="list-style-type: none"> • Connectable conductor cross-section for signal line, min. • Connectable conductor cross-section for signal line, max. • Connectable conductor cross-section for AWG cables, min. • Connectable conductor cross-section for AWG cables, max. <p>0.05 mm² 1.5 mm² 30 16</p>
Dimensions	
Width	73 mm
Height	199 mm
Depth	46 mm
Weights	
Weight (without packaging)	0.49 kg
last modified:	1/16/2021 

