



Figure similar

SIPLUS S7-300 SM 331 AI 8x0/4...20mA based on 6ES7331-7TF01-0AB0 with conformal coating, -25...+70 °C,

General information	
based on	6ES7331-7TF01-0AB0
Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	20 mA
from backplane bus 5 V DC, max.	120 mA
output voltage / header	
supply voltage of the transmitters / header	
• Rated value (DC)	24 V
Power loss	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	8
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
• Voltage	No
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	240 Ω
• -20 mA to +20 mA	
— Input resistance (-20 mA to +20 mA)	240 Ω
• 4 mA to 20 mA	
— Input resistance (4 mA to 20 mA)	240 Ω
Cable length	
• shielded, max.	800 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Integration time (ms)	20 ms at 50 Hz; 16.6 ms at 60 Hz; 100 ms at 100 Hz
• Interference voltage suppression for interference	10 / 50 / 60 Hz

frequency f1 in Hz

Encoder

Connection of signal encoders

- for current measurement as 2-wire transducer Yes
- for current measurement as 4-wire transducer Yes

Errors/accuracies

Operational error limit in overall temperature range

- Current, relative to input range, (+/-) 0.15 %; ±0.25 % @ < 0 °C or > 60 °C

Basic error limit (operational limit at 25 °C)

- Current, relative to input range, (+/-) 0.1 %

Interrupts/diagnostics/status information

Diagnostics function Yes

Alarms

- Diagnostic alarm Yes
- Limit value alarm Yes

Diagnoses

- Diagnostic information readable Yes

Diagnostics indication LED

- Group error SF (red) Yes

Potential separation

Potential separation analog inputs

- between the channels No
- between the channels, in groups of 8
- between the channels and backplane bus Yes
- between the channels and the power supply of the electronics Yes

Isolation

Isolation tested with 500

Standards, approvals, certificates

CE mark Yes

UL approval Yes; File E239877

RCM (formerly C-TICK) Yes

KC approval Yes

EAC (formerly Gost-R) Yes

Railway application

- EN 50121-4 No
- EN 50155 No

Ambient conditions

Ambient temperature during operation

- min. -25 °C; = Tmin
- max. 70 °C; = Tmax; 60 °C @ UL/cUL use

Ambient temperature during storage/transportation

- min. -40 °C
- max. 70 °C

Altitude during operation relating to sea level

- Installation altitude above sea level, max. 5 000 m
- Ambient air temperature-barometric pressure-altitude Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

Relative humidity

- With condensation, tested in accordance with IEC 60068-2-38, max. 100 %; RH incl. condensation/frost (no commissioning under condensation conditions)

Resistance

Use in stationary industrial systems

- to biologically active substances according to EN 60721-3-3 Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
- to chemically active substances according to EN 60721-3-3 Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
- to mechanically active substances according to EN 60721-3-3 Yes; Class 3S4 incl. sand, dust, *

Use on ships/at sea

- to biologically active substances according to EN 60721-3-6 Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request

— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
connection method	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	205 g
last modified:	5/29/2024 