



SIMOTION Drive-based Control Unit D410-2 DP/PN; programmable single-axis motion controller with multi-axis option; interfaces: 5 DI, 8 DI/DO, 3 F-DI, 1 F-DO, 1 AI, 1 encoder, 1 DRIVE-CLiQ, 1 PROFIBUS, 2 PROFINET ports, 1 ethernet Note: requires at least SCOUT/firmware V4.3 SP1 HF3

| | |
|--------------------------------------|-------------------------------------------|
| product brand name | SIMOTION |
| product type designation | D410-2 DP/PN |
| Version of the motion control system | Single-axis system with multi-axis option |

PLC and motion control performance

| | |
|-----------------------------------|--------------------------------------------------------------------------|
| number of axes / maximum | 8 |
| Minimum PROFIBUS cycle clock | 1 ms |
| Minimum PROFINET send cycle clock | 0.25 ms |
| Minimum interpolator cycle clock | 0.5 ms |
| Minimum servo cycle clock | 0.5 ms |
| • note | 1 ms when using the TO axis and the integrated closed-loop drive control |

Integrated drive control / header

| | |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Maximum number of axes for integrated drive control | |
| • servo | 1 |
| • vector | 1 |
| • V/f | 1 |
| • note | Alternative control modes; drive control based on SINAMICS S120 CU310-2, firmware version V4.x/V5.x |

Memory

| | |
|--------------------------------------------------|-----------|
| RAM (work memory) | 122 Mbyte |
| Additional RAM work memory for Java applications | 20 Mbyte |
| RAM disk (load memory) | 60 Mbyte |
| Retentive memory | 108 kbyte |
| Persistent memory (user data on CF) | 1.5 Gbyte |

Communication

| | |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Interfaces | |
| • DRIVE-CLiQ | 1 |
| • Industrial Ethernet | 1 |
| • PROFIBUS | 1 |
| — note | Equidistant and isochronous; Can be configured as master or slave |
| • PROFINET | 1 |
| — note | Interface with 2 ports; supports PROFINET IO with IRT and RT; configurable as PROFINET IO Controller and/or Device; supports media redundancy (MRP and MRPD) |

General technical data

| | |
|----------------------------|-------------------------------------------------------------------|
| Fan | Integrated |
| DC supply voltage | |
| • rated value | 24 V |
| • minimum | 20.4 V |
| • maximum | 28.8 V |
| consumed current / typical | 800 mA |
| • note | with no load on inputs/outputs, no 24 V supply via DRIVE-CLiQ and |

| | |
|-------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Making current, typ. | PROFIBUS interface |
| Power loss, typ. | 3 A |
| Ambient temperature, during | 20 W |
| • long-term storage | -25 ... +55 °C |
| • transport | -40 ... +70 °C |
| • operation | 0 ... 55 °C |
| — note | Maximum installation altitude 4000 m (13124 ft) above sea level. Above an altitude of 2000 m (6562 ft), the maximum ambient temperature decreases by 7 °C (12.6 °F) per 1000 m (3281 ft). |
| Relative humidity | |
| • during operation | 5 ... 95 % |
| • without condensation, tested acc. to IEC 60068-2-38 | Wert fehlt |
| Air pressure | 620 ... 1 060 hPa |
| Degree of protection | IP20 / UL open type |
| height | 190.7 mm |
| width | 73 mm |
| • depth | 74.4 mm |
| net weight | 830 g |

Digital inputs / header

| | |
|------------------------------------------------|------------------------------------|
| number of digital inputs | 11 |
| Digital inputs / note | of which: 5 DI and 3 F-DI (= 6 DI) |
| DC input voltage | |
| • rated value | 24 V |
| • for signal "1" | 15 ... 30 V |
| • for signal "0" | -3 ... +5 V |
| Electrical isolation | Yes |
| Current consumption for "1" signal level, typ. | 3.5 mA |
| Input delay time for | |
| • signal "0" → "1", typ. | 50 µs |
| • signal "1" → "0", typ. | 150 µs |

Digital inputs/outputs / header

| | |
|--------------------------------------------------|-----------------------------------------------------------------------------------------|
| Number of digital I/Os | 8 |
| Parameterization possibility of the digital I/Os | can be parameterized - as DI - as DO - as probe input (max. 8) - as cam output (max. 8) |

If used as an input / header

| | |
|------------------------------------------------|---------------|
| DC input voltage | |
| • rated value | 24 V |
| • for signal "1" | 15 ... 30 V |
| • for signal "0" | -3 ... +5 V |
| Electrical isolation | No |
| Current consumption for "1" signal level, typ. | 3.5 mA |
| Input delay time for | |
| • signal "0" → "1", typ. | 5 µs |
| • signal "1" → "0", typ. | 50 µs |
| Measuring input / reproducibility | 5 µs |
| • note | typical value |
| Measuring input / resolution | 1 µs |

If used as an output / header

| | |
|-------------------------------------------------|--------------------------------------------------------------------|
| Load voltage | |
| • rated value | 24 V |
| • minimum | 20.4 V |
| • maximum | 28.8 V |
| Electrical isolation | No |
| Current carrying capacity for each output, max. | 500 mA |
| Leakage current, max. | 2 mA |
| Output delay for | |
| • signal "0" → "1", typ. | 150 µs |
| • signal "0" → "1", max. | 400 µs |
| • signal "1" → "0", typ. | 75 µs |
| • signal "1" → "0", max. | 100 µs |
| — note | Data for Vcc = 24 V; load 48 Ohm; "1" = 90 % VOut, "0" = 10 % VOut |

| | |
|------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Cam output | |
| • reproducibility | 125 µs |
| — note | typical value |
| • resolution | 125 µs |
| — note | typical value |
| Switching frequency of the outputs for | |
| • resistive load, max. | 100 Hz |
| • inductive load, max. | 0.5 Hz |
| • lamp load, max. | 10 Hz |
| Short-circuit protection | Yes |
| Digital outputs / header | |
| Number of digital outputs | 1 |
| Parameterization possibility of the digital outputs | can be parameterized as F-DO or DO |
| Load voltage | |
| • rated value | 24 V |
| • minimum | 20.4 V |
| • maximum | 28.8 V |
| Electrical isolation | Yes |
| Current carrying capacity for each output, max. | 500 mA |
| Leakage current, max. | 2 mA |
| Output delay for | |
| • signal "0" → "1", typ. | 150 µs |
| • signal "0" → "1", max. | 400 µs |
| • signal "1" → "0", typ. | 75 µs |
| • signal "1" → "0", max. | 100 µs |
| — note | Data for Vcc = 24 V; load 48 Ohm; "1" = 90 % VOut, "0" = 10 % VOut |
| Short-circuit protection | Yes |
| Analog inputs / header | |
| number of analog inputs | 1 |
| If used as an voltage input / header | |
| Input voltage | -10 ... +10 V |
| Resolution | 12 bit |
| • note | +sign |
| Input resistance (Ri) | 100 kΩ |
| If used as an current input / header | |
| Input current | -20 ... +20 mA |
| Resolution | 11 bit |
| • Note | + sign |
| Input resistance (Ri) | 250 Ω |
| Onboard encoder interface / header | |
| Encoder interface | optional incremental encoder TTL, incremental encoder HTL or absolute encoder SSI without incremental signals TTL/HTL |
| Encoder supply for | |
| • 24 VDC | 0.35 A |
| • 5 VDC | 0.35 A |
| Limiting frequency, max. | 500 kHz |
| SSI baud rate | 100 ... 1 000 |
| Resolution of absolute position SSI | 30 bit |
| Cable length for | |
| • TTL incremental encoder, max. | 100 m |
| • HTL incremental encoder for | |
| — unipolar signals, max. | 100 m |
| — bipolar signals, max. | 300 m |
| — note | TTL only bipolar signals; for bipolar signals, the signal lines must be twisted in pairs and shielded |
| • SSI absolute encoder, max. | 100 m |
| — note | max. cable length depends on the baud rate |
| Additional technical data | |
| design of the sensor / to detect the ambient temperature / connectable | KTY84-130, PT1000 or PTC |
| Back-up of non-volatile data | |
| • of retentive data | unlimited buffer duration |
| • of real-time clock, min. | 5 d |

- note

Approvals

- USA
- Canada
- Australia
- Korea
- Russia, Belarus and Kazakhstan

Data buffering is maintenance-free

cULus

cULus

RCM (formerly C-Tick)

KCC

EAC

