## 6ES7132-4BB31-0AA0

**Data sheet** 



SIMATIC DP, 5 electronic modules for ET 200S, 2 DO Standard 24 V DC/2 A, 15 mm width, 5 units per packing unit

Supply voltage	
Reverse voltage protection	Yes; when using the same load voltage as on the power module
Load voltage L+	
<ul><li>Rated value (DC)</li></ul>	24 V; From power module
Reverse polarity protection	Yes; polarity reversal can lead to the digital outputs being connected through
Input current	
from load voltage L+ (without load), max.	5 mA; Per channel
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	1.4 W
Address area	
Address space per module	
<ul> <li>Address space per module, max.</li> </ul>	1 byte
<ul><li>with packing</li></ul>	2 bit
Digital outputs	
Type of digital output	Source output (PNP, current-sourcing)
Number of digital outputs	2
Short-circuit protection	Yes
<ul> <li>Response threshold, typ.</li> </ul>	2.8 to 7.2 A
Limitation of inductive shutdown voltage to	-55 to -60 V, typ. L+( )
Controlling a digital input	Yes
Switching capacity of the outputs	
<ul><li>on lamp load, max.</li></ul>	10 W
Load resistance range	
lower limit	12 Ω
• upper limit	3 400 Ω
Output voltage	
● for signal "1", min.	L+ (-1 V)
Output current	
<ul><li>for signal "1" rated value</li></ul>	2 A
<ul><li>for signal "1" permissible range, min.</li></ul>	7 mA
<ul><li>for signal "1" permissible range, max.</li></ul>	2.4 A
<ul><li>for signal "0" residual current, max.</li></ul>	0.5 mA
Output delay with resistive load	
• "0" to "1", max.	200 μs
• "1" to "0", max.	1.3 ms
Parallel switching of two outputs	
<ul><li>for uprating</li></ul>	No
<ul> <li>for redundant control of a load</li> </ul>	Yes; per module
Switching frequency	

	100 11
<ul> <li>with resistive load, max.</li> </ul>	100 Hz
<ul><li>with inductive load, max.</li></ul>	2 Hz; 0,5 H
on lamp load, max.	10 Hz
Total current of the outputs	
Current per module, max.	4 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	No
Diagnostics indication LED	
<ul> <li>Status indicator digital output (green)</li> </ul>	Yes
Parameter	
Remark	1 byte
Potential separation	
Potential separation digital outputs	
<ul> <li>between the channels</li> </ul>	No
<ul> <li>between the channels and backplane bus</li> </ul>	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	40 g

2/9/2021

last modified: