SIEMENS

Data sheet

6ES7132-4BD32-0AA0



SIMATIC DP, 5 electronic modules for ET 200S, 4 DO standard 24 V DC/2 A, 15 mm width, 5 units per packing unit

Figure similar

Supply voltage	
Reverse voltage protection	Yes; when using the same load voltage as on the power module
Load voltage L+	
 Rated value (DC) 	24 V; From power module
 Reverse polarity protection 	Yes
Input current	
from load voltage L+ (without load), max.	10 mA; Per channel
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	1.6 W
Address area	
Address space per module	
Address space per module, max.	1 byte
with packing	4 bit
Digital outputs	
Type of digital output	Source output (PNP, current-sourcing)
Number of digital outputs	4
Short-circuit protection	Yes
 Response threshold, typ. 	2.8 to 7.2 A
Limitation of inductive shutdown voltage to	Typ. L+ (-55 to -60 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
on lamp load, max.	10 W
Load resistance range	
• lower limit	12 Ω
• upper limit	3 400 Ω
Output voltage	
● for signal "1", min.	L+ (-1.0 V)
Output current	
• for signal "1" rated value	2 A
• for signal "1" permissible range, min.	7 mA
for signal "1" permissible range, max.	2.4 A
● for signal "0" residual current, max.	0.1 mA
Output delay with resistive load	
• "0" to "1", max.	50 μs; Typ. 45 μs
• "1" to "0", max.	120 µs; Typ. 90 µs
Parallel switching of two outputs	
• for uprating	No
 for redundant control of a load 	Yes; per module

Switching frequency	
 with resistive load, max. 	1 000 Hz
 with inductive load, max. 	2 Hz; At 0.5 H
on lamp load, max.	10 Hz
Total current of the outputs	
Current per module, max.	4 A
Cable length	
shielded, max.	1 000 m
unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	No
Diagnostics indication LED	
 Status indicator digital output (green) 	Yes
Parameter	
Remark	1 byte
Potential separation	
Potential separation digital outputs	
 between the channels 	No
 between the channels and backplane bus 	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	40 g

last modified:

9/22/2023