

SIMATIC DP, interface DP/PA-Link and ET200M IM153-2 HF for extended temperature range for max. 12 S7-300 modules with redundancy capability, Timestamping suitable for isochronous mode New features: up to 12 modules can be used Slave Initiative for Drive ES and Switch ES Expanded quantity structure for HART auxiliary variables Operation of the 64-channel modules 32 signals / slot +++ Observe compatibility instructions in manual +++

General information	
Product type designation	IM 153-2 OD
Firmware version	V6.1
Vendor identification (VendorID)	801Eh
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2,5 A
Mains buffering	
<ul style="list-style-type: none"> Mains/voltage failure stored energy time 	5 ms
Input current	
Current consumption, max.	650 mA
Inrush current, typ.	3 A
I^2t	0.1 A ² ·s
Output current	
for backplane bus (5 V DC), max.	1.5 A
Power loss	
Power loss, typ.	5.5 W
Address area	
Addressing volume	
<ul style="list-style-type: none"> Inputs 	244 byte
<ul style="list-style-type: none"> Outputs 	244 byte
Hardware configuration	
number of modules per DP device interface, max.	12
Time stamp	
Accuracy	1 ms; 1 ms at up to 8 modules; 10 ms at up to 12 modules
Number of message buffers	15
Messages per message buffer	20
Number of stampable digital inputs, max.	128; Max. 128 signals/station; max. 32 signals/slot
Time format	RFC 1119
Time resolution	0.466 ns
Time interval for transmitting the message buffer if a message is present	1 000 ms
Time stamp on signal change	rising / falling edge as signal entering or exiting
Interfaces	
Transmission procedure	RS 485
Transmission rate, max.	12 Mbit/s
1. Interface	
automatic detection of transmission rate	Yes
Interface types	
<ul style="list-style-type: none"> Output current of the interface, max. Design of the connection 	70 mA 9-pin sub D socket
PROFIBUS DP device	
<ul style="list-style-type: none"> GSD file automatic baud rate search 	SI05801E.GSG Yes

Protocols	
Bus protocol/transmission protocol	PROFIBUS DP to EN 50170
PROFIBUS DP	
• Number of node addresses, max.	1 to 125 permitted
Services	
— SYNC capability	Yes
— FREEZE capability	Yes
— Direct data exchange (slave-to-slave communication)	Yes; as publisher with all IO, as subscriber with F-IO only
Potential separation	
Potential separation exists	Yes
Isolation	
Isolation tested with	Isolation voltage 500 V
Degree and class of protection	
IP degree of protection	IP20
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-25 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-25 °C
• vertical installation, max.	40 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	3 000 m
Configuration	
Configuration software	
• STEP 7	Yes; STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	360 g

Classifications			
		Version	Classification
	eClass	14	27-24-26-08
	eClass	12	27-24-26-08
	eClass	9.1	27-24-26-08
	eClass	9	27-24-26-08
	eClass	8	27-24-26-08
	eClass	7.1	27-24-26-08
	eClass	6	27-24-26-08
	ETIM	10	EC001604
	ETIM	9	EC001604
	ETIM	8	EC001604
	ETIM	7	EC001604
	IDEA	4	3564
	UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	

[Manufacturer Declaration](#)



[Miscellaneous](#)



[China RoHS](#)



General Product Ap-	For use in hazardous locations
---------------------	--------------------------------

proval



[Type Examination Certificate](#)

[FM](#)



For use in hazardous locations Maritime application Environment

[CCC-Ex](#)



[CCS \(China Classification Society\)](#)



last modified:

4/7/2025