



SIMATIC PS307/1AC/DC24V/5A/Outdoor

SIMATIC S7-300 Outdoor Regulated power supply PS307 input: 120/230 V AC, output: 24 V/5 A DC

input	
type of the power supply network	1-phase AC
supply voltage at AC	Set by means of selector switch on the device
supply voltage	120 V/230 V
input voltage 1 at AC	93 ... 132 V
input voltage 2 at AC	187 ... 264 V
wide range input	No
overvoltage overload capability	$2.3 \times V_{in}$ rated, 1.3 ms
buffering time for rated value of the output current in the event of power failure minimum	20 ms
operating condition of the mains buffering	at $V_{in} = 93/187$ V
line frequency	50/60 Hz
line frequency	47 ... 63 Hz
input current	
• at rated input voltage 120 V	2.1 A
• at rated input voltage 230 V	1.2 A
current limitation of inrush current at 25 °C maximum	45 A
duration of inrush current limiting at 25 °C	
• maximum	3 ms
I ² t value maximum	1.8 A ² ·s
fuse protection type	T 3,15 A/250 V (not accessible)
fuse protection type in the feeder	Recommended miniature circuit breaker: from 10 A characteristic C or from 6 A characteristic D
output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	
• at output 1 at DC rated value	24 V
output voltage adjustable	No; -
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
• on slow fluctuation of input voltage	0.2 %
• on slow fluctuation of ohm loading	0.4 %
residual ripple	
• maximum	150 mV
• typical	40 mV
voltage peak	
• maximum	240 mV
• typical	90 mV
display version for normal operation	Green LED for 24 V OK

behavior of the output voltage when switching on	No overshoot of Vout (soft start)
response delay maximum	3 s
voltage increase time of the output voltage	
• typical	100 ms
output current	
• rated value	5 A
• rated range	0 ... 5 A
supplied active power typical	120 W
short-term overload current	
• on short-circuiting during the start-up typical	20 A
• at short-circuit during operation typical	20 A
duration of overloading capability for excess current	
• on short-circuiting during the start-up	180 ms
• at short-circuit during operation	80 ms
bridging of equipment	No
efficiency	
efficiency in percent	84 %
power loss [W]	
• at rated output voltage for rated value of the output current typical	23 W
closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.3 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	3 %
setting time	
• load step 50 to 100% typical	0.2 ms
• load step 100 to 50% typical	0.2 ms
setting time	
• maximum	5 ms
protection and monitoring	
design of the overvoltage protection	Additional control loop, shutdown at approx. 30 V, automatic restart
property of the output short-circuit proof	Yes
design of short-circuit protection	Electronic shutdown, automatic restart
response value current limitation	5.5 ... 6.5 A
enduring short circuit current RMS value	
• maximum	5 A
safety	
galvanic isolation between input and output	Yes
galvanic isolation	Safety extra low output voltage Vout according to EN 60950-1 and EN 50178, creepage distances and clearances > 5 mm
operating resource protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	0.3 mA
protection class IP	IP20
EMC	
standard	
• for emitted interference	EN 55011 Class A
• for mains harmonics limitation	-
• for interference immunity	EN 61000-6-2
standards, specifications, approvals	
certificate of suitability	
• CE marking	Yes
• UL approval	Yes; UL-Listed (UL 508), File E143289; CSA (CSA C22.2 No. 142)
• CSA approval	Yes; UL-Listed (UL 508), File E143289, CSA (CSA C22.2 No. 142)
• EAC approval	Yes
• NEC Class 2	No
type of certification	
• CB-certificate	No
MTBF at 40 °C	2 231 610 h

standards, specifications, approvals hazardous environments	
certificate of suitability	
• IECEx	No
• ATEX	No
• ULhazloc approval	No
• cCSAus, Class 1, Division 2	No
• FM registration	No
standards, specifications, approvals marine classification	
shipbuilding approval	No
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• French marine classification society (BV)	No
• Det Norske Veritas (DNV)	No
• Lloyds Register of Shipping (LRS)	No
standards, specifications, approvals Environmental Product Declaration	
Environmental Product Declaration	Yes
Global Warming Potential [CO2 eq]	
• total	731.2 kg
• during manufacturing	11.2 kg
• during operation	719.5 kg
• after end of life	0.36 kg
ambient conditions	
ambient temperature	
• during operation	-25 ... +70; with natural convection
• during transport	-40 ... +85
• during storage	-40 ... +85
environmental category according to IEC 60721	Climate class 3K5, transient condensation permitted
connection method	
type of electrical connection	screw terminal
• at input	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded
• at output	L+, M: 3 screw terminals each for 0.5 ... 2.5 mm ²
• for auxiliary contacts	-
mechanical data	
width × height × depth of the enclosure	80 × 125 × 120 mm
installation width × mounting height	80 mm × 225 mm
required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
fastening method	Can be mounted onto S7 rail
• standard rail mounting	No
• S7 rail mounting	Yes
• wall mounting	No
housing can be lined up	Yes
net weight	0.57 kg
accessories	
mechanical accessories	Mounting adapter for standard mounting rail (6ES7390-6BA00-0AA0)
further information internet links	
internet link	
• to website: Industry Mall	https://mall.industry.siemens.com
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to website: CAX-Download-Manager	https://siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
additional information	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber

threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Classifications

	Version	Classification
eClass	14	27-04-07-01
eClass	12	27-04-07-01
eClass	9.1	27-04-07-01
eClass	9	27-04-07-01
eClass	8	27-04-90-02
eClass	7.1	27-04-90-02
eClass	6	27-04-90-02
ETIM	9	EC002540
ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

Approvals Certificates

General Product Approval	Test Certificates	other
--------------------------	-------------------	-------



[Confirmation](#)



[Type Test Certificates/Test Report](#)

[Confirmation](#)

other	Environment
Miscellaneous	Environmental Confirmations

last modified: 11/19/2024