



Figure similar

SIMATIC DP, HART analog input SM 331, 8 AI, 0/4 - 20 mA HART, for ET200M with IM153-2, 1 x 20-pole, Functions: FW update, HART auxiliary variables, redundancy, local diagnostic buffer with time stamping,

General information	
Product function	
• Isochronous mode	No
Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	20 mA
from backplane bus 5 V DC, max.	120 mA
output voltage / header	
supply voltage of the transmitters / header	
• product function / supply voltage for transmitters	Yes
• supply voltage / of the transmitters / at DC / rated value	24 V
• product feature / of the supply voltage for transmitters / short-circuit proof	Yes
• supply current / from supply voltage for transmitter / maximum	60 mA
Power loss	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	8
permissible input current for current input (destruction limit), max.	40 mA
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	140 Ω
• -20 mA to +20 mA	
— Input resistance (-20 mA to +20 mA)	140 Ω
• 4 mA to 20 mA	
— Input resistance (4 mA to 20 mA)	140 Ω
Cable length	
• shielded, max.	800 m
Analog value generation for the inputs	
Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Integration time (ms)	20 ms at 50 Hz; 16.6 ms at 60 Hz; 100 ms at 100 Hz

• Basic conversion time, including integration time (ms) • Interference voltage suppression for interference frequency f1 in Hz	55 ms @ 60 Hz, 65 ms @ 50 Hz, 305 ms @ 100 Hz 10 / 50 / 60 Hz
Smoothing of measured values	
• parameterizable • Step: None • Step: low • Step: Medium • Step: High	Yes Yes Yes Yes Yes
Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer • for current measurement as 4-wire transducer	Yes Yes
Errors/accuracies	
Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	0.15 %
Basic error limit (operational limit at 25 °C)	
• Current, relative to input range, (+/-)	0.1 %
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm • Limit value alarm	Yes Yes
Diagnostics indication LED	
• Group error SF (red) • Channel fault indicator F (red)	Yes Yes
Potential separation	
Potential separation analog inputs	
• between the channels • between the channels and backplane bus	No Yes
Isolation	
Isolation tested with	500 V DC
Degree and class of protection	
IP degree of protection	IP20
connection method / header	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	205 g
last modified:	4/1/2022 