

SIEMENS

Data sheet for SINUMERIK Machine control panel



Figure similar

MLFB-Ordering data 6FC5303-0AF23-0AA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data		Ambient conditions	
Input voltage	DC 24 V	Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).	
Power consumption, max.	21.2 W		
Mechanical data		Ambient temperature	
Net weight	1.200 kg (2.65 lb)	Operation on the front	0 ... 45 °C (32 ... 113 °F)
Width	310.0 mm (12.20 in)	Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Height	175.0 mm (6.89 in)	Transport	-40 ... 70 °C (-40 ... 158 °F)
Depth	85.2 mm (3.35 in)	Storage	-25 ... 55 °C (-13 ... 131 °F)
Installation depth	With connector for handwheel connection	Relative humidity	
	Without connector for handwheel connection	Operation	5 ... 95 %
Mounting surface		Storage	5 ... 95 %
Cutout width	285.0 mm (11.22 in)	Transport	5 ... 95 %
Cutout height	155.0 mm (6.10 in)	Approvals	
Degree of protection		Certificate of suitability	CE, cULus
Rear side	IP00		
Front side	IP54		
	Key-operated switch IP54		