



SCALANCE XC106-2, Unmanaged IE switch, 6x 10/100 Mbit/s RJ45 ports, 2x 100 Mbit/s Multimode BFOC, LED diagnostics, error-signaling contact with set pushbutton, redundant power supply Manual available as a download .

| | |
|---|-----------------------|
| product type designation | SCALANCE XC106-2 |
| transfer rate | |
| transfer rate | 10 Mbit/s, 100 Mbit/s |
| interfaces / for communication / maximum configuration for modular devices | |
| number of electrical ports / maximum | 6 |
| number of optical ports / maximum | 2 |
| interfaces / for communication / integrated | |
| number of electrical connections | |
| • for network components or terminal equipment | 6; RJ45 |
| number of 100 Mbit/s ST(BFOC) ports | |
| • for multimode | 2 |
| interfaces / other | |
| number of electrical connections | |
| • for signaling contact | 1 |
| • for power supply | 1 |
| type of electrical connection | |
| • for signaling contact | 2-pole terminal block |
| • for power supply | 4-pole terminal block |
| signal inputs/outputs | |
| operating voltage / of the signaling contacts | |
| • at DC / rated value | 24 V |
| operational current / of the signaling contacts | |
| • at DC / maximum | 0.1 A |
| supply voltage, current consumption, power loss | |
| product component / connection for redundant voltage supply | Yes |
| type of voltage / 1 / of the supply voltage | |
| • supply voltage / 1 / rated value | DC |
| • power loss [W] / 1 / rated value | 24 V |
| • consumed current / 1 / at rated supply voltage / maximum | 4.8 W |
| • supply voltage / 1 / rated value | 0.4 A |
| • type of electrical connection / 1 / for power supply | 9.6 ... 31.2 V |
| • product component / 1 / fusing at power supply input | 4-pole terminal block |
| • fuse protection type / 1 / at input for supply voltage | Yes |
| ambient conditions | |
| ambient temperature | |
| • during operation | -40 ... +70 °C |
| • during storage | -40 ... +85 °C |
| • during transport | -40 ... +85 °C |
| relative humidity | |
| • at 25 °C / without condensation / during operation / | 95 % |

| | |
|--|--|
| maximum protection class IP | IP20 |
| design, dimensions and weights | |
| design | compact |
| width | 60 mm |
| height | 147 mm |
| depth | 125 mm |
| net weight | 0.5 kg |
| material / of the enclosure | Polycarbonate (PC-GF10) |
| fastening method | |
| • 35 mm top hat DIN rail mounting | Yes |
| • wall mounting | Yes |
| • S7-300 rail mounting | Yes |
| • S7-1500 rail mounting | Yes |
| product features, product functions, product components / general | |
| number of automatically learnable MAC addresses | 2048 |
| product functions / management, configuration, engineering | |
| product function | |
| • multiport mirroring | No |
| • CoS | Yes |
| product function / switch-managed | No |
| product function | |
| • is supported / identification link | Yes; according to IEC 61406-1:2022 |
| product functions / redundancy | |
| product function | |
| • Parallel Redundancy Protocol (PRP)/operation in the PRP-network | Yes |
| • Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) | No |
| standards, specifications, approvals | |
| standard | |
| • for safety / from CSA and UL | UL 60950-1, CSA C22.2 No. 60950-1 |
| • for emitted interference | EN 61000-6-4 (Class A) |
| reference code | |
| • according to IEC 81346-2 | KF |
| • according to IEC 81346-2:2019 | KFE |
| standards, specifications, approvals / CE | |
| certificate of suitability / CE marking | Yes |
| standards, specifications, approvals / hazardous environments | |
| standard / for hazardous zone | EN 60079-0:2012 + A11:2013, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X, IEC 6079-0:2011, IEC 6079-0-15:2010 |
| • from CSA and UL | UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T.., Class 1 / Zone 2 / Group IIC / T.. |
| certificate of suitability | |
| • CCC / for hazardous zone according to GB standard | Yes; GB3836.1, GB3836.8 |
| • CCC / for hazardous zone according to GB standard / as marking | Ex nA IIC T4 Gc |
| standards, specifications, approvals / other | |
| laser protection class | LED Class 1 |
| certificate of suitability | EN 61000-6-2, EN 61000-6-4 |
| • C-Tick | Yes |
| • KC approval | Yes |
| • E1 approval | No |
| • EC Declaration of Conformity EN 61010, IEC 61010-1, UL 61010A-1 | Yes |
| standards, specifications, approvals / marine classification | |
| Marine classification association | |
| • American Bureau of Shipping Europe Ltd. (ABS) | Yes |
| • French marine classification society (BV) | Yes |
| • DNV GL | Yes |
| • Korean Register of Shipping (KRS) | Yes |
| • Lloyds Register of Shipping (LRS) | Yes |

- Polski Rejestr Statków (PRS)
- Royal Institution of Naval Architects (RINA)

Yes

Yes

standards, specifications, approvals / Environmental Product Declaration

| | |
|--|-----------|
| Environmental Product Declaration | Yes |
| • Global Warming Potential [CO2 eq] / total | 220.3 kg |
| • Global Warming Potential [CO2 eq] / during manufacturing | 32.08 kg |
| • Global Warming Potential [CO2 eq] / during operation | 187.75 kg |
| • global warming potential [CO2 eq] / after end of life | 0.48 kg |

further information / internet links

| | |
|---------------|---|
| internet link | <ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Selection guide for cables and connectors • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support |
| | <p>http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter https://sie.ag/2QdIxcP http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com</p> |

security information

| | |
|----------------------|--|
| security information | <p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial security concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial security measures that may be implemented, please visit https://www.siemens.com/industrialsecurity. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Security RSS Feed under https://www.siemens.com/cert. (V4.6)</p> |
|----------------------|--|

Approvals / Certificates

| | |
|--------------------------|-----|
| General Product Approval | EMC |
|--------------------------|-----|

[Manufacturer Declaration](#)



[Miscellaneous](#)



For use in hazardous locations

Marine / Shipping



IECEx



ATEX

FM

[CCC-Ex](#)



ABS



BUREAU
VERITAS

Marine / Shipping

other



LRS

[NK / Nippon Kaiji Kyōkai](#)



PRS



RINA



KR
KOREAN REGISTER
OF SHIPS

[Manufacturer Declaration](#)

Environment

[Confirmation](#)

[Environmental Con-](#)
[firmations](#)

last modified:

11/9/2023 